











Gauged porcelain tile panels require specialized installation products to ensure full mortar coverage and a lifetime of low-maintenance beauty.

While this brochure highlights several options designed specifically for gauged porcelain tile panels, other solutions may be available. Contact your MAPEI representative for more information.





Surface prep

Planitop 330 Fast | Ultraplan Easy | Mapecem Quickpatch





	Product Code	Packaging
U.S. / Canada	223523	Bag: 50 lbs. (22.7 kg)

Planitop® 330 Fast

Flattening walls is fast and easy with this fiber-reinforced wall render and vertical patch.

- · For interior/exterior walls and floors
- \cdot 1/8" to 1-1/4" (3 mm to 3.2 cm) in thickness in a single coat
- Fast drying allows tile installation in 90 minutes with no shrinking.







	Product Code	Packaging
U.S. / Canada	24350000	Bag: 50 lbs. (22.7 kg)

Ultraplan® Easy

It's rare to find a floor that meets the GPT flatness requirement of 1/8" (3 mm) variation within 10 feet (3.05 m). *Ultraplan Easy* lets you simply clean, prime and pour, and you're ready to tile in 3 to 4 hours.

- · Interior, quick-setting self-leveling underlayment
- · Featheredge to 2" (5 cm) in thickness
- \cdot High-strength; can withstand light foot traffic in 2 to 3 hours after installation







	Product Code	Packaging
U.S. / Canada	10510000	Bag: 10 lbs. (4.54 kg)
	10525000	Bag: 25 lbs. (11.3 kg)
	10550	Bag: 50 lbs. (22.7 kg)

Mapecem® Quickpatch

For smaller repairs or troweling, *Mapecem Quickpatch* provides a moisture-resistant solution.

- · For interior/exterior concrete surfaces
- \cdot 1/16" to 3" (1.5 mm to 7.5 cm) in thickness
- $\boldsymbol{\cdot}$ Sets fast for easy and cost-efficient patching







	Product Code	Color	Packaging
U.S./	1201511	Gray	Bag: 25 lbs. (11.3 kg)
Canada	1201611	White	Bag: 25 lbs. (11.3 kg)
Canada	1201511C	Gray	Bag: 25 lbs. (11.3 kg)
	1201611C	White	Bag: 25 lbs. (11.3 kg)





	Product Code	Color	Packaging
U.S.	11250000	Gray	Bag: 50 lbs. (22.7 kg)
	11350000	White	Bag: 50 lbs. (22.7 kg)
Canada	1125000021	Gray	Bag: 25 lbs. (11.3 kg)
	113500021	White	Bag: 25 lbs. (11.3 kg)





	Product Code	Packaging
U.S. / Canada	3584615	Pail: 4 U.S. gals. (15.1 L)





	Product Code	Packaging
U.S.	3961001	Kit: 3 U.S. gals. (11.4 L)
Canada	396100121	Kit: 3 U.S. gals. (11.4 L)

MAPEI Ultralite™ S2

Combining lightweight technology with a lower water ratio for faster curing, *MAPEI Ultralite S2* is a smart choice.

- · Lightweight and single-component
- · High-performance and highly deformable
- Long open time, extended coverage and superior transfer properties to enhance back-buttering, which is ideal for thin porcelain tiles
- · Exceeds ANSI A118.4HE and ANSI A118.15HE

ISO 13007 C2ES2P2











Ultraflex™ LFT™

Still the industry leader for large-format tile, *Ultraflex LFT* stands up to the rigors of setting large and heavy tiles.

- Non-sag for installing large-format and heavy tile; allows bond coats up to 1/2" (12 mm) thick
- · Polymer-enriched for high-performance adhesion and deformability
- · Formulated with Easy Glide Technology™ for ease of application
- Exceeds ANSI A118.4HTE and ANSI A118.15HTE

ISO 13007 C2TES1P1









Ultrabond ECO® GPT

This innovative, hybrid-polymer-based adhesive technology saves time and effort when installing panels/slabs on walls.

- · Non-sag performance with panels
- · Ready to use, with no mixing required
- · Smooth consistency and easy to trowel
- · High bond strength and deformability

Kerapoxy® 410

When only the best will do, *Kerapoxy 410* bonds to urethane/epoxy mesh backings, exterior walls and everywhere in between.

- · Solvent-free, 100%-solids, epoxy setting floor and wall mortar that is suited for areas where the most chemical-resistant setting material is necessary
- Has high compressive strength, which provides excellent impact strength in commercial facilities
- · Designed for setting most types of tile and stone, including moisture-sensitive stone
- Exceeds ANSI A118.3

ISO 13007 R2







	Product Code	Packaging
U.S. / Canada	6BU0XXX05* 6BU0XXX11*	Bag: 10 lbs. (4.54 kg) Bag: 25 lbs. (11.3 kg)





	Product Code	Packaging
U.S. /	5XX01 and 4KA0XXX04*	Pail: 1 U.S. gal. (3.79 L)
Canada	5XX02 and 4KA0XXX08*	Pail: 2 U.S. gals. (7.57 L)





	Product Code	Packaging
U.S./	4XX92 and 5UB0XXX58*	1 U.S. qt. (946 mL)
Canada	4XX52 and 5UB0XXX04*	1 U.S. gal. (3.79 L)
	4XX59 and 5UB0XXX08*	2 U.S. gals. (7.57 L)





	Product Code	Packaging
U.S./	3BT00XX91 and	Cartridge: 10.1 U.S. oz. (299 mL)
Canada	3BT0XXX91*	

Ultracolor® Plus FA

Small grout joints are no problem for the fine aggregate in *Ultracolor Plus FA* grout.

- For joint widths from 1/16" to 3/4" (1.5 to 19 mm)
- Fine-aggregate, fast-setting, polymer-modified, color-consistent, nonshrinking, efflorescence-free grout
- DropEffect[™] technology reduces surface absorption to help repel water, dirt and grime from penetrating grout joints.

ISO 13007 CG2WAF











 $^{^*}$ For the "XXX" portion of the product code, use the three-digit number of the desired grout color.

MAPEI Flexcolor® CQ

For the ultimate in color consistency and installation speed, *MAPEI Flexcolor CQ* grout has you covered.

- For joint widths from 1/16" to 1/2" (1.5 to 12 mm)
- Ready-to-use with quartz aggregate, which ensures color consistency, ease of cleanability and improved workability
- Can be used on sensitive tile surfaces once tested, requires no sealer and cures naturally from evaporation of the low level of water in the formulation



^{*} For the "XX" and "XXX" portions of the product code, use the two- or three-digit number of the desired grout color.

Kerapoxy® CQ

As a grout highly resistant to stains, traffic and most chemicals, *Kerapoxy CQ* grout also protects the delicate edges of gauged tiles.

- For joint widths from 1/16" to 3/8" (1.5 to 10 mm)
- Two-component, 100%-solids epoxy grout and mortar that is non-sagging/ nonslumping
- · Resistant to stain/chemicals, easy to maintain, water-cleanable and easy to apply

ISO 13007 R2/RG







^{*} For the "XX" and "XXX" portions of the product code, use the two- or three-digit number of the desired grout color.

Mapesil™ T

Color-matched to MAPEI's grouts, *Mapesil T* can be used in every joint if needed, including soft joints to accommodate movement.

- · 100%-silicone sealant for use on multiple substrates
- · Specifically formulated for heavy traffic and expansion/movement joints
- · Exceeds ASTM and ANSI standards



^{*} For the "XX" and "XXX" portions of the product code, use the two- or three-digit number of the desired grout color.



HIGH-PERFORMANCE SYSTEMS WITH BUILT-IN CONFIDENCE



MAPEI's System Warranties

System warranties from MAPEI provide enhanced coverage, including replacement product and reimbursement of associated replacement costs. When considering a system warranty, the customer and the MAPEI representative should review the MAPEI products applicable for each category of the installation – such as surface preparation, waterproofing, mortars and grouts. For any installation exceeding 10,000 square feet (929 m²), contact MAPEI's Technical Services Department to confirm the system recommendations.

Special Circumstance Warranties

Commercial and residential contractors can contact their distributor to locate a MAPEI sales representative, who can provide a project warranty when it is a required contract document. All project warranties must be requested prior to the start of the installation.







Videos from MAPEI Technical Institute

Look for new and informative MTI-TV videos on MAPEI's Website or find them on the YouTube channel for MAPEI USA or MAPEI Canada.



MAPEI Headquarters of North America

1144 East Newport Center Drive Deerfield Beach, Florida 33442 1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

1-800-992-6273 (U.S. and Puerto Rico) 1-800-361-9309 (Canada)

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Copyright ©2020 by MAPEI Corporation ("MAPEI") and all rights are reserved. All intellectual property rights and other information contained in this document are the exclusive property of MAPEI (or its parent or related companies), unless otherwise noted. No part of this document may be reproduced or transmitted in any form without the prior written consent of MAPEI.

Printed in the USA.

