

Light weight... Heavy performance

MAPEI Ultralite™ Mortar Pro

FEATURES AND BENEFITS

- The product's Easy Glide Technology™ provides a smooth and creamy application.
- Ultralite Technology™ means a 25-lb. (11.3-kg) bag of this mortar offers the same coverage as 50 lbs. (22.7 kg) of a standard thin-set mortar.
- This thin-set mortar is nonsag/nonslump for large and heavy tile.
- For thicker bond coats from 3/32" to 1/2" (2.5 to 12 mm)
- Contains more than 20% recycled content



Learn more



MAPEI USA





DESCRIPTION

MAPEI *Ultralite Mortar Pro* is a professional-grade, lightweight, single-component thin-set mortar that can also be used for large-and-heavy-tile and nonsag applications. This polymer-modified mortar is formulated with Easy Glide Technology™ for ease of application. MAPEI *Ultralite Mortar Pro*'s unique Ultralite Technology™ provides twice the coverage of a standard thin-set mortar per pound/kg and contains more than 20% recycled content.

FEATURES AND BENEFITS

- Polymer-enriched for enhanced bond performance
- Nonsag/honslump thin-set formula for large and heavy tile/stone
- 25-lb. (11,3-kg) bag of MAPEI *Ultralite Mortar Pro* provides the same coverage as a 50-lb. (22,7-kg) bag of a standard polymer-modified mortar
- Smooth and creamy consistency

INDUSTRY STANDARDS AND APPROVALS

- ISO 13007: Classification C1TES1
- ANSI: Exceeds ANSI A118.4HET and ANSI A118.11 bond strength requirements
- SCS Green Squared Certified per ANSI A138.1

WHERE TO USE

- Most interior/exterior residential installations on floors and walls
- Most interior/exterior commercial installations on floors
- Most interior commercial installations on walls
- Installation of ceramic and porcelain tile, quarry tile, pavers, Saltillo tile, large-format tile and most types of marble, granite and natural stone



SHELF LIFE AND APPLICATION PROPERTIES*

at 73°F (23°C) and 50% relative humidity

Shelf life	1 year
Open time*	30 minutes
Pot life*	> 2 hours
Time before grouting*	24 hours
VOCs (Rule #1168 of California's SCAQMD)	0 g per L

* Actual open time, pot life and time before grouting will vary based on jobsite conditions.

APPROXIMATE COVERAGE**

Typical Trowel		Coverage
For thin-set applications		
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm)		75 to 90 sq. ft. (6.97 to 8.36 m ²)
1/4" x 3/8" x 1/4" (6 x 10 x 6 mm)		55 to 65 sq. ft. (5.11 to 6.04 m ²)
Large-and-heavy-tile and nonsag applications for walls and floors		
1/2" x 1/2" x 1/2" (12 x 12 x 12 mm)		38 to 45 sq. ft. (3.53 to 4.18 m ²)
3/4" x 9/16" x 3/8" (19 x 14 x 10 mm)		25 to 30 sq. ft. (2.32 to 2.79 m ²)

** Trowel dimensions are width/depth/space. Actual coverages will vary according to substrate profile and tile type.

PACKAGING

U.S. 2429211	Bag: 25 lbs. (11.3 kg), gray
U.S. 2429311	Bag: 25 lbs. (11.3 kg), white