

UltraCare[®]

Smooth Silicone

WITHOUT

WITH **ULTRACARE
SMOOTH SILICONE**

Finishing spray solution for smoothing of sealants



DESCRIPTION

UltraCare Smooth Silicone is a water-based, innovative spray solution suitable for silicone and urethane sealants as well as acrylic and latex caulks. It increases the speed and ease of finishing the sealant during application and contributes to creating smooth, compact surfaces that will reduce dirt pick-up and the formation of mold. It is suitable for use with sealants and caulks during installation of ceramic tile, porcelain tile, stone and glass tile.

FEATURES AND BENEFITS

- Ready to use
- Effective for use on silicone/urethane sealants and acrylic/latex caulks
- Increases the speed and ease of sealant application
- Helps with finishing and shaping of sealant joints
- Low-odor, low-VOC, water-based formula
- Non-residue formulation safe for ceramic, porcelain, stone and glass surfaces
- Non-corrosive; will not damage metal trims and profiles

This advanced formulation ensures a low-odor, low-VOC application, making it beneficial for both the user and the environment. Its non-corrosive composition protects metal trims and profiles, while its non-residue feature guarantees a clean finish on ceramic, porcelain, stone and glass surfaces.

Watch
the demo.



— MAPEI USA • MAPEI Caribe —



SHELF LIFE AND PRODUCT CHARACTERISTICS

Shelf life	Up to 3 years when stored in original, unopened packaging at 73°F (23°C). Freeze/thaw-stable.
Appearance	Clear
Odor	Slight odor
Physical state	Liquid
VOC content (California Air Resources Board's Consumer Products Regulation, Section 94509)	< 5% by weight
Typical VOC content per California Air Resources Board testing methods	1.80% by weight

PACKAGING

Size

Spray bottle: 24 U.S. oz. (710 mL)

APPROXIMATE COVERAGE* per 24 U.S. oz. (710 mL)


Coverage

1,000 linear feet (305 m)


** Coverage is heavily influenced by the type of sealant and the method of application.*



READY TO USE



INCREASES THE
SPEED OF SEALANT
APPLICATION



HELPS WITH
FINISHING OF
SEALANT JOINTS

