

UltraCare Heavy-Duty Stone, Tile & Grout Cleaner



DESCRIPTION

UltraCare® Heavy-Duty Stone, Tile & Grout Cleaner is a highly concentrated and high-alkaline cleaner and degreaser. This product is formulated to quickly remove most waxes, grease, oil, light soap scum, and stains from mildew and algae. It is quite effective at removing most factory-applied waxes and floor finishes, and is ideal for areas that have been neglected or subject to heavy use.

FEATURES AND BENEFITS

- Removes most wax, grease, soap scum, body oil, mildew stains and algae
- Ideal for neglected areas or areas subjected to heavy use
- Specially formulated to strip off synthetic and acrylic waxes and floor finishes

WHERE TO USE

- Most natural stones, grout, ceramic, porcelain, terra cotta, Saltillo, quarry tiles, terrazzo, concrete, pavers and masonry surfaces

LIMITATIONS

- Ensure that product does not come in contact with any non-recommended surface.
- Regular use of high-alkaline cleaners will affect the performance of sealers applied on surfaces.

Consult MAPEI's Technical Services Department for application recommendations regarding substrates and conditions not listed.

PRODUCT APPLICATION

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

Always test first in several inconspicuous areas to confirm desired results.

1. Sweep, vacuum or wipe the surface to be cleaned.
2. Dilute with water as follows: a) For light cleaning: Mix 8 parts water to 1 part cleaner; b) For moderate cleaning: Mix 4 parts water to 1 part cleaner; c) For heavy cleaning and stripping wax: Mix 2 parts water to 1 part cleaner.
3. Working in a small, manageable area of about 15 sq. ft. (1,39 m²), liberally apply the solution to the surface with a sponge or a mop.
4. Allow the product to stand on the surface for at least 5 minutes for cleaning or 10 minutes for stripping. Do not allow the product to dry on the surface. Keep wet by adding more solution to the surface.
5. Scrub with a white nylon pad, scrub brush or scrub machine.
6. Remove the dirty solution with a wet vac or mop.
7. Rinse thoroughly with clean water.
8. Do not track cleaning residue into adjacent areas.
9. Repeat the process as necessary.
10. Allow at least 48 hours of drying time before applying *UltraCare* sealers and finishes.

Close container tightly after each use. Store in original container only. Store between temperatures of 35°F and 90°F (2°C and 32°C). Do not allow to freeze.

Shelf Life and Application Properties

Shelf life	Up to 5 years when stored in the original sealed container. Freeze/thaw-stable.
Appearance	Light beige liquid
Odor	Slight odor
Physical state	Liquid
VOCs	34 g per L

Packaging

Size
Bottle: 1 U.S. qt. (946 mL)
Jug: 1 U.S. gal. (3,79 L)

Approximate Coverage*

Size	Coverage
1 U.S. qt. (946 mL)	50 to 150 sq. ft. (4,65 to 13,9 m ²)
1 U.S. gal. (3,79 L)	200 to 600 sq. ft. (18,6 to 55,7 m ²)

*Coverage will vary depending on the dilution ratio used; the density, porosity and texture of the surface; how long the solution is left on a surface; the application method; and the severity of the cleaning required.

ADDITIONAL INFORMATION

Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: October 24, 2023 MK 3000208 (23-1999)

For the most current product data and BEST-BACKEDSM warranty information, visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.

