

Mapeheat Cable Guides

Snap-Together Cable Guides for Customizable Radiant-Heated Floors



Technology from



DESCRIPTION

Mapeheat™ Cable Guides are used to secure *Mapeheat Cable* to a substrate before installation of floor-covering materials (tile, stone, laminate, engineered wood or luxury vinyl flooring). *Mapeheat Cable Guides* can be attached to a wooden subfloor with nails or screws, and to a concrete subfloor with hot glue.

Installing *Mapeheat Cable* with *Mapeheat Cable Guides* offers flexible spacing for varying watt density as follows:

- Consistent 3" (7.5 cm) spacing produces 12 W/ft² (standard output).
- Alternating spacing of 3" and 2" (7.5 and 5 cm) produces 15 W/ft² (high output), which is best for installations on a concrete slab or when heat loss is a concern.

Product Specifications

| | |
|-----------------|----------------------|
| Color | Red |
| Material | Plastic |
| Guides per pack | 12 |
| Patent | U.S. Patent D664,098 |

Number of Guides Required

| Cable length | Guides required (1 pack contains 12 guides) |
|---------------------------------|--|
| 0 to 60 ft. (0 to 18.3 m) | 1 pack |
| 60 to 120 ft. (18.3 to 36.6 m) | 2 packs |
| 121 to 190 ft. (36.9 to 57.9 m) | 3 packs |
| 190 to 260 ft. (57.9 to 79.2 m) | 4 packs |
| 260 to 340 ft. (79.2 to 104 m) | 5 packs |
| 340 to 420 ft. (104 to 128 m) | 6 packs |
| 420 to 500 ft. (128 to 152 m) | 7 packs |
| 500 to 590 ft. (152 to 180 m) | 8 packs |
| 590 to 680 ft. (180 to 207 m) | 9 packs |
| 680 to 770 ft. (207 to 235 m) | 10 packs |
| 770 to 870 ft. (235 to 265 m) | 11 packs |
| 870 to 970 ft. (265 to 296 m) | 12 packs |

RELATED DOCUMENTS

*Mapeheat Cable Installation Handbook**

*At www.mapei.com

ADDITIONAL INFORMATION

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: June 6, 2023 MK 3000359 (22-2614)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.

