

- Ready-to-use
- Resistant to light foot traffic
- Up to 24 months shelf life in its original packaging
- For exposed continuous waterproofing layers
- Quick, easy installation
- Waterproof
- Flexible with high crack-bridging properties
- Excellent bond on a multitude of surfaces
- High resistance to atmospheric agents
- Non-toxic and non-flammable



- PRODUCTS FOR CERAMICS AND STONE MATERIALS
- PRODUCTS FOR RESILIENT AND TEXTILE MATERIALS
- PRODUCTS FOR WOODEN FLOORING
- PRODUCTS FOR CEMENTITIOUS AND RESIN FLOORING
- PRODUCTS FOR ACOUSTIC INSULATION
- PRODUCTS FOR BUILDING
- ADMIXTURES FOR CONCRETE
- PRODUCTS FOR STRUCTURAL STRENGTHENING
- PRODUCTS FOR THE REPAIR OF MASONRY
- PRODUCTS FOR THERMAL INSULATION
- WALL PROTECTIVE AND DECORATIVE COATINGS
- PRODUCTS FOR WATERPROOFING
- PRODUCTS FOR UNDERGROUND CONSTRUCTIONS
- ELASTIC SEALANTS AND ADHESIVES
- GRINDING AIDS FOR CEMENT

C.P. MK692530 (GB) 10/11

Aquaflex Roof



Can it be any easier than this?

Ready-to-use flexible liquid membrane with fibres for continuous waterproofing layers on exposed external surfaces



HEADQUARTERS
 MAPEI SpA
 Via Cafiero, 22 - 20158 Milan
 Tel. +39 02 37673.1
 Fax +39 02 37673.214
 Internet: www.mapei.com
 E-mail: mapei@mapei.it



www.mapei.com

ADHESIVES - SEALANTS - CHEMICAL PRODUCTS FOR BUILDING

Aquaflex Roof

Ready-to-use flexible liquid membrane with fibres for continuous waterproofing layers on exposed external surfaces

WHERE TO USE

Waterproof exposed surfaces for:

- flat roofs;
- balconies and terraces;
- guttering and downpipes;
- cupolas and curved roofs.

AQUAFLEX ROOF MAY BE APPLIED ON:

- ceramic and stone coatings;
- cementitious screeds and screeds made using special binders (**Topcem** and **Topcem Pronto**);
- concrete;
- asbestos cement;
- bitumen sheaths;
- wood.



An example of old terracotta floor requiring treatment before applying **Aquaflex Roof**



Waterproofing fraction joints with **Mapeband** fixed with **Aquaflex Roof**



Cleaning a substrate before applying **Aquaflex Roof**



Application of **Aquaflex Roof** with a long-haired roller

Technical Data	
Product identity	
Consistency:	paste
Colours:	brick red, grey
Density (kg/m ³):	1,32
Dry solids content (%):	62
Application data	
Application temperature range:	from +5°C to +35°C
Waiting time between first and second coat:	approx. 8-12 hours
Set to light foot traffic:	12 hours at +23°C
Final performance	
Elongation at breakage (DIN 53504) (%):	300
Tensile strength (DIN 53504) (N/mm ²):	1.1
Packaging:	20 kg drums
Consumption:	1.3 kg/m ² per mm of thickness

