



PLANIPATCH XTRA

Ultra-fast drying, thixotropic cementitious patching compound for local repairs.





Planipatch Xtra

DESCRIPTION

Ultra-fast, rapid drying, thixotropic cementitious compound for local repairs.

Ultra-fast, moisture tolerant, rapid drying patching compound for the local repairs for interior floors, walls, steps and corners where a quick hardening and drying, together with a particular smooth final finish is required.

POT LIFE	(approx) 10 mins	READY FOR USE	(approx) 60 mins
SET TO LIGHT FOOT TRAFFIC	(approx) 45-60 mins	STORAGE	12 months
COLOUR	Grey	PACKAGING	5kg bags


AREAS OF USE




VERY GOOD WORKABILITY



HIGH BOND STRENGTH



CAN BE TROWELLED TO A FEATHER EDGE



CAN BE APPLIED UP TO 25MM

WHERE TO USE

- Filling voids, holes, and cracks in the substrates (provided they are stable)
- Fast edging or local repairing before a final smoothing with suitable self-levelling compounds
- Patching and local repairs of stairs, landings, and edges of columns
- Can be used over heated floors
- When mixed with **Latex Plus, Planipatch Xtra** can be used for feathering or patching properly prepared metal and wood surfaces, old substrates with residues of paints, resin, and bitumen-based adhesive residues, fully adhered resilient and wood flooring
- When mixed with **Latex Plus, Planipatch Xtra** can be used to feather over new raised access flooring panels, if they are clean from any contamination and are stable with regards to movement
- Stone, ceramic and Terrazzo tiles

CERTIFICATIONS & TECHNOLOGIES



www.blauer-engel.de/uz113





MAPEI UK LTD

Mapei House
Steel Park Road
Halesowen
West Midlands, B62 8HD
0121 508 6970
info@mapei.co.uk

MAPEI WORLD LONDON CITY

6 Great Sutton Street
Clerkenwell
London
EC1V 0BX
020 3302 9610
clerkenwell@mapei.co.uk