



A blue roller is shown applying a primer to a concrete surface. The roller is covered in a thick layer of blue primer, and it is being pushed across the surface. The background is a textured concrete surface. A blue rectangular box is overlaid on the right side of the image, containing the product name and description. A red horizontal bar is located below the blue box.

MAPEPROOF PRIMER

ONE-COMPONENT, RAPID DRYING
PVDC BASED DISPERSION PRIMER FOR
SUPPRESSING RESIDUAL MOISTURE

ONE-COMPONENT, RAPID DRYING PVDC BASED DISPERSION PRIMER



PRIMER IMPERMEABILIZZANTE
MONOCOMPONENTE
IN DISPERSIONE ACQUOSA, A BASE DI PVDC,
PER UMIIDITÀ RESIDUA FINO A 4,5 CM-% (95% UR)
ONE-COMPONENT, RAPID DRYING PVDC BASED
DISPERSION MEMBRANE FOR SUPPRESSING
RESIDUAL MOISTURE UP TO 4.5 CM-% (95% R.H.)
RESIDUAL MOISTURE UP TO 4.5 CM-% (95% R.H.)
EINKOMPONENTIGE, SCHNELL TROCKNENDE,
FEUCHTIGKEITSSPERRENDE
DISPERSIONSGRUNDIERUNG FÜR
ZEMENTESTRICH BIS 4,5 CM-% (95% R.L.)
PRIMER IMPERÉABILISANT MONOCOMPOSANT,
À DISPERSION AQUEUSE, À BASE DE PVDC,
POUR UNE HUMIDITÉ RÉSIDUELLE
JUSQU'À 4,5 CM-% (95% HR)



www.blauer-engel.de/uz113

Mapeproof Primer



WHERE TO USE:

- Damp-proofing cement
- Moisture-resistant substrates
- For substrates with underfloor heating where residual moisture content values are up to 2.5 CM-% (85% R.H.).
- Residential
- Commercial
- Industrial sectors

Mapeproof Primer is a one component, ready to use system which dries rapidly to provide a waterproof surface membrane; it impedes the passage of residual construction moisture from affecting subsequent floorcovering installations, therefore allowing early installation of floorcoverings.

PROPERTIES OF THE PRODUCT:

- Ready for use, no mixing is required
- Easy to apply by roller
- Colour pigmented to aid coverage uniformity
- Fast Drying
- Low consumption/high coverage
- No primer or sprinkling sand is required
- Not inflammable
- Can be resealed and stored with no particular precautions for future use

TECHNICAL DATA: (4.5 CM-% (95% R.H.))

PRODUCT IDENTITY	
Consistency:	Fluid liquid
Colour:	Green
Drying time:	15-30 minutes for the first coat, Second coat allow 30 minutes
Waiting time:	2-5 hours, max 12 hours
Application temperature range:	From +5°C to +35°C
Storage:	12 months in its original sealed packaging
Consumption:	Approx. 250 g/m ² as a two coats application
Packaging:	10kg can

MAPEI WORLD LONDON CITY

6 Great Sutton Street
Clerkenwell
London
EC1V 0BX
020 3302 9610
clerkenwell@mapei.co.uk

MAPEI UK LTD

Mapei House
Steel Park Road
Halesowen
West Midlands. B62 8HD
0121 508 6970
info@mapei.co.uk



0121 508 6970 | mapei.co.uk

