## **Associated Products**

## COMPLETE YOUR PROJECT WITH...

### **Surface Primers**

Eco Prim T

**Eco Prim Grip** 





### **Eco Adhesives**



## **Damp Proof Membranes**

Mapeproof ESM

**Mapeproof One Coat** 

Mapeproof 1k Turbo







## Latexplan Trade Fast

Two-part rapid curing, smoothing & levelling compound







# Latexplan Trade Fast

#### **Technical Data**

PRODUCT IDENTITY	
Colour:	Part A) Grey Part B) White liquid
Consistency:	Part A) Fine Powder Part B) Runny Liquid

COMPOSITION & PROPERTIES OF THE MIXTURE	
Mixing Ratio:	4kg of Part B (liquid) with 20kg of Part A (powder)
Thickness per coat:	3mm to 10mm
Application Range Temps:	+5°C to +35°C
Pot Life:	25 minutes
Setting Time:	30 minutes
Set to light foot traffic:	60 minutes
Time before installing floorcoverings:	2 hours 30 mins to 3 hours

For more technical information please visit our website www.mapei.co.uk and search for 'Latexplan Trade Fast' in the product search box.

#### Where to use

**Latexplan Trade** *Fast* is used for levelling and smoothing differences in thickness of 3mm to 10mm (in one application) where rapid installation of all types of floor coverings is required on new and existing substrates.

With low odour emissions and a setting time of 30 minutes, **Latexplan Trade** *Fast* is an excellent solution for any time constrained project.

### **Advantages**

- Rapid installation of all types of floor coverings on both new and existing substrates.
- Suitable for high intensity/wheelchair traffic.
- Latexplan Trade Fast is suitable for smoothing sand cement screeds including Mapecem and Topcem screeds. It is also suitable for smoothing terazzo, ceramic, porcelain tiles and natural stone (after applying a suitable primer to the surface if required).
- Suitable for use within confined or inhabited areas due to its very low odour release, a perfect solution when working and/or occupation must be maintained.

