

MAPELEVEL EASY SYSTEM

Quick-thread screw
levelling system for ceramic
and stone floor and wall tiling





MapeLevel Easy System

With **MapeLevel Easy** tile levelling system, achieving a perfect floor is even easier and faster. Thanks to the **rapid screwing** system, **MapeLevel Easy** can be applied more quickly, considerably reducing overall installation time.

Tile **levelling** is even more **precise**: this allows to prevent any tile lippage guaranteeing a perfect result, even when laying large format tiles.

Versatile and complete, **MapeLevel Easy System** can be used with a wide range of tiles (up to 21 mm thick) and adapts to all laying patterns, with lower consumption rates compared with the traditional wedge systems.

MapeLevel Easy System is mainly made of recycled plastic material, respecting the environment.



Where to use

- For ceramic tiles and stone slabs on floors and walls.
- Particularly recommended for the installation of large format tiles.
- For tiles from 3 to 21 mm thick.

System set



Cap
MapeLevel Easy Cap



Spacer
MapeLevel Easy Spacer L
A complete range of screw spacers, available in 3 versions (linear, T and X spacers) and 5 different sizes (1, 1.5, 2, 3, 5 mm).



Anti-scratch shield
MapeLevel Easy Shield
Optional accessory: to be applied under the cap to protect the surface of delicate tiles.



Before application



After application



An installation with several **advantages**



Rapid screwing

Thanks to the special rapid-thread screw, the cap spins down the screw faster and with less effort, making the application quicker.



Manual installation and removal

MapeLevel Easy can be installed and removed by hand, without screwers, unscrewers or additional tools.




Easy levelling

Tiles can be levelled easily and precisely by simply tightening the cap until obtaining a perfectly flat tiling.



A complete range of spacers

Available in 3 versions and 5 different thicknesses to suit all application requirements. **MapeLevel Easy Spacers L** are designed to break off below the surface of the tile, for a quick and accurate removal.



Consumption table



Open-view cap design

The exclusive shape of **MapeLevel Easy Cap**, with wide lateral openings, allows the installer to check the tile levelling.




Reusable cap

The disposable elements are easily removed from the caps, which can be used again to install other tiling.

Approximate number of caps and spacers required for an area of 10 m².


A																			
10	1980																		
15	1317	876																	
20	495	328	490																
25	396	263	391	312															
30	660	438	488	389	431														
40	495	328	365	291	322	240													
45	440	292	324	258	285	213	189												
50	396	263	291	232	256	191	169	152											
60	330	219	242	193	212	158	141	126	105										
75	396	263	258	206	212	158	140	126	104	99									
80	371	246	241	192	198	148	131	117	97	93	87								
90	330	219	214	171	176	131	116	104	86	82	77	68							
100	297	197	192	153	157	117	104	93	77	73	68	61	54						
120	330	219	200	160	157	117	104	93	77	71	66	59	52	49					
150	330	219	192	153	146	109	96	86	71	64	60	53	47	44	38				
180	330	219	186	149	139	103	91	82	68	60	56	49	44	40	34	31			
200	347	230	192	153	140	104	92	83	68	59	55	49	44	39	33	30	28		
cm	10	15	20	25	30	40	45	50	60	75	80	90	100	120	150	180	200	B	

Linear installation



A																			
10	980																		
15	650	431																	
20	485	322	240																
25	386	256	191	152															
30	320	212	159	126	105														
40	485	322	240	191	159	178													
45	430	286	213	170	141	157	140												
50	386	256	191	152	126	141	125	112											
60	320	212	159	126	105	117	104	93	77										
75	387	256	191	152	126	125	111	99	82	81									
80	362	240	179	143	118	117	103	93	77	76	71								
90	321	213	159	126	105	103	92	82	68	67	63	56							
100	287	190	142	113	94	92	82	73	60	60	56	50	44						
120	321	213	159	126	105	96	85	76	63	60	56	49	44	43					
150	321	213	159	126	105	92	82	73	60	55	52	46	41	38	34				
180	321	213	159	126	105	89	79	71	59	52	49	43	38	36	31	28			
200	337	223	167	133	110	92	81	73	60	53	49	44	39	35	30	27	26		
cm	10	15	20	25	30	40	45	50	60	75	80	90	100	120	150	180	200	B	

Cross joint installation



Consumption rates are approximate and depend on the layout and flatness of the tiles.

EVERYTHING'S OK,
WITH MAPEI

HEAD OFFICE
MAPEI SpA
Via Cafiero, 22
20158 Milan
+39-02-37673.1
mapei@mapei.it
mapei.com

