

Crack-bridging	
+23 °C (EN 14891-A.8.2)	3.1 mm
-5 °C (EN 14891-A.8.3)	2.0 mm
<b>-20 °C</b> (EN 14891-A.8.3)	0.9 mm













## 

Ready-to-use, one-component, ultra-quick drying flexible liquid membrane

for waterproofing under ceramic, marble and mosaics, for

interior and exterior







- One-component, ready-to-use
- Quick drvina
- No reinforcement required
- Rain fast after just 3 hours
- Tiles installation after just 4 hours with suitable adhesive
- Rooms treated with the product back in use after just 1 day
- **Leed Italy** credits: up to 2 points for regional materials



24 months



## Where and how to use

Waterproofing balconies, terraces, bathrooms, shower booths and damp environments before laying coatings Applied by roller, brush or trowel

May be used and re-used with no waste if kept in its original packaging

Mapelastic AquaDefense may be used with the special pieces of Mapelastic System:

Mapeband (90°, 270°, T, CROSS), Mapeband TPE (T, CROSS), Drain Vertical, Drain Lateral, Drain Front

## Properties of the product

Consumption: 1 kg/m² for two coats (1.3 kg/m<sup>2</sup> per mm of thickness) 15 kg package, suitable for covering 15 m<sup>2</sup> Storage time in original packaging:

