# **Associated Products**

# Ultrabond Eco 4 LVT

**Fibre-reinforced Luxury** 

**Vinyl Tile Adhesive** 

#### **COMPLETE YOUR PROJECT WITH...**

### Surface Primers

Eco Prim T

Eco Prim Grip





## **Smoothing Compounds**

Ultraplan Eco



**Ultraplan Renovation Screed** 

MK707730 06/14







# **Damp Proof Membranes**

Mapeproof ESM

Mapeproof One Coat

Mapeproof 1k Turbo











Luxury Vinyl Flooring Adhesive Ultrabond Eco 4 LVT Smoothing compound Ultraplan Eco Primer Eco Prim T

Substrate Topcem Pronto







Mapei House, Steel Park Road, Halesowen, West Midlands. B62 8HD Tel. 0121 508 6970 Website: www.mapei.co.uk E-mail: info@mapei.co.uk

# Ultrabond Eco 4 LVT



## **Technical Data**

PRODUCT IDENTITY	
Colour:	Light Beige
Consistency:	Creamy Paste
pH level:	7.5
EMICODE:	EC1 Plus - Very Low Emission

APPLICATION DATA (at +25°C - 50% R.H.)	
Application Range Temps:	+15°C to +35°C
Waiting Time:	10 minutes
Open time:	Maximum 30 - 40 minutes
Set to light foot traffic:	3 to 4 hours
Ready for use:	48 hours
Resistance to moisture:	Good
Resistance to ageing:	Excellent
Resistance to solvents and oils:	Good
Resistance to temperature:	Excellent
Underfloor heating systems:	Suitable

For more technical information please visit our website www.mapei.co.uk and search for 'Ultrabond Eco 4 LVT' in the product search box.



#### Where to use

**Ultrabond Eco 4 LVT** is used for bonding internal LVT floors, PVC and semi-flexible vinyl tiles on all kinds of conventional absorbent substrates stable in the presence of humidity, normally used in the building industry.

#### **Advantages**

• **Ultrabond Eco 4 LVT** is a solvent-free, fibre-reinforced synthetic polymer-based adhesive in water dispersion.

• It is available in paste form which is easy to spread by trowel and is, in particular, used to bond LVT floor-covering materials.

• **Ultrabond Eco 4 LVT** stands out because it is extremely easy to spread and has a very high initial bond, which fixes the flooring fast to the substrate.

• When hardened, **Ultrabond Eco 4 LVT** forms a tough, flexible film which allows for an excellent bond on all kinds of substrates. It may also be used for floors subject to heavy pedestrian use, the passage of wheelchairs and for heated floors.

