



MAPEPAVE

Mortar and Slurry for use in external tiling applications





MapePave Mortar

DESCRIPTION

Pre-blended, ready to use mortar with normal setting and controlled shrinkage for fast-drying bedding. Use in conjunction with MapePave Slurry.

TECHNICAL DATA

Consistency: powder.
Colour: grey.
Bulk density (kg/m³): 1,500.
Density of the mix (kg/m³): 2,100 depending on compaction.
Mix ratio: 1.55 - 1.8 litres of water.
Mixing time: 5-10 mins.
Workability of the mix: 60 mins

Application temperature range: from +5°C to +35°C.
Set to light foot traffic: after approx. 12 hours.
Ready for use: after approx. 4 days.
Storage: 12 months.
Consumption: 15 kg/m² per cm of thickness.
Packaging: 25kg bags.

MAIN FEATURES



Walkable after 12 hours

WHERE TO USE



MapePave Slurry

DESCRIPTION

Pre-blended, ready to use mortar, mixed with water for a paving slurry ideal for bonding 20mm porcelain. Use in conjunction with MapePave Mortar.

TECHNICAL DATA

Consistency: fluid.
Colour: grey.
Bulk density (kg/m³): 1,500.
Mix ratio: 6.2 - 6.4 litres of water.
Mixing time: 5-10 mins.
Workability of the mix: 60 mins.
Open time: 10 mins.

Application temperature range: from +5°C to +30°C.
Set to light foot traffic: after approx. 12 hours.
Ready for use: after approx. 4 days.
Storage: 12 months.
Consumption: approx. 6m² per 20kg bag.
Packaging: 20kg bags.

MAIN FEATURES



Walkable after 12 hours

WHERE TO USE





MAPEI UK LTD

Mapei House
Steel Park Road
Halesowen
West Midlands, B62 8HD
0121 508 6970
info@mapei.co.uk

MAPEI WORLD LONDON CITY

6 Great Sutton Street
Clerkenwell
London
EC1V 0BX
020 3302 9610
clerkenwell@mapei.co.uk