

DECLARATION OF PERFORMANCE N. UKCA-GB1/0010

- 1) Unique identification code of the product-type: **ULTRAPLAN RENOVATION SCREED 3240**
- 2) Intended uses: **Cementitious screed material for internal use in floor construction**
- 3) Manufacturer: **MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD- www.mapei.co.uk**
- 4) Systems of AVCP: **System 4**
System 3 for reaction to fire
- 5) Designated standards: **EN 13813 :2002**

Approved bodies: **Warringtonfire 0833**
- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class E/E_{fl}
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C25
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Peter Dube – Head of HSEQ**

Halesowen, 14/07/2021



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 as amended from time to time and as it has effect in the United Kingdom in respect of Great Britain are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website.

<i>Revision 0 notes:</i>	<i>First issue</i>
--------------------------	--------------------

ULTRAPLAN RENOVATION SCREED 3240**UK MARKING****Annex to DoP N. UKCA - GB1/0010**

	 MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD www.mapei.co.uk
21 UKCA - GB1/0010 EN 13813 ULTRAPLAN RENOVATION SCREED 3240 <i>Cementitious screed material for internal use in floor construction</i>	
Reaction to fire:	Class E/E _{fl}
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C25
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the UK marking easier for the international clients. The enclosed UK marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the UK marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries,
- the product is already in stock when the updating of the UK marking is implemented,
- printing mistakes.