

DECLARATION OF PERFORMANCE N. CPR-GB1/0002

- 1) Unique identification code of the product-type: **ADESILEX P9**
- 2) Intended uses: **improved cementitious adhesive for internal and external tiling on floors and walls**
- 3) Manufacturer: **MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD- www.mapei.co.uk**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 12004:2007+A1:2012**

Notified bodies:

**Technische Universität München Materialprüfungsamt für das Bauwesen, N. 1211
and Instytut Techniki Budowlanej (ITB), N. 1488**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire: Bond strength: Durability against: - climate/heat ageing action: - water/humidity action: - freeze-thaw cycles: Release of dangerous substances:	Class A1/ A1_{fl} expressed as: - initial tensile adhesion strength $\geq 1,0 \text{ N/mm}^2$ expressed as: - tensile adhesion strength after heat ageing $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after water immersion $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after freeze-thaw cycles $\geq 1,0 \text{ N/mm}^2$ NPD

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Dube – Head of HSEQ

Halesowen, 03/08/2021





REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website

Revision 1 notes:	Product unchanged, the new DoP layout has been adopted
--------------------------	---

ADESILEX P9
CE MARKING
Annex to DoP N. CPR-GB1/0002



 1211 1488	 MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD www.mapei.co.uk
04 CPR-GB1/0002 EN 12004 ADESILEX P9 <i>improved cementitious adhesive for internal and external tiling on floors and walls</i>	
Reaction to fire: Bond strength: Durability against: - climate/heat ageing action: - water/humidity action: - freeze-thaw cycles: Release of dangerous substances:	Class A1/ A1 _{fl} expressed as: - initial tensile adhesion strength $\geq 1,0 \text{ N/mm}^2$ expressed as: - tensile adhesion strength after heat ageing $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after water immersion $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after freeze-thaw cycles $\geq 1,0 \text{ N/mm}^2$ NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values can be omitted by the CE marking*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*