

MAPEKER RAPID SET FLEX
CE MARKING
Annex to DoP N. CPR-GB1/0014



CE
1211
1488



MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen,
West Midlands B62 8HD
www.mapei.co.uk

05
CPR-GB1/0014
EN 12004

MAPEKER RAPID SET FLEX

improved fast setting cementitious adhesive for internal and external tiling on floors and walls

Reaction to fire:	Class A1/ A1 _{fl}
Bond strength:	expressed as: - initial tensile adhesion strength $\geq 1,0$ N/mm ² - early tensile adhesion strength $\geq 0,5$ N/mm ²
Durability against:	expressed as:
- climate/heat ageing action:	- tensile adhesion strength after heat ageing $\geq 1,0$ N/mm ²
- water/humidity action:	- tensile adhesion strength after water immersion $\geq 1,0$ N/mm ²
- freeze-thaw cycles:	- tensile adhesion strength after freeze-thaw cycles $\geq 1,0$ N/mm ²
Release of dangerous substances:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values can be omitted by the CE marking*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*