

Eco Prim T

EASY / **PRO** / **PLUS**

START WITH THE RIGHT CHOICE.



Any installation work gets a better start with **Eco Prim T**: the multi-purpose line of acrylic primers with the lowest VOC emission, perfect for any site. Super-rapid drying times, maximum ease of application and high performance for a practical, quick job, and always with respect for the health and the environment.



EVERYTHING'S **OK**
WITH **MAPEI**

Learn more on mapei.com



ECO PRIM T line



		ECO PRIM T PLUS Universal acrylic primer	ECO PRIM T PRO Multipurpose acrylic primer	ECO PRIM T EASY Ready-to-use acrylic primer
		Maximum dilution		
WHERE TO USE	Cementitious screeds	1:4	1:2	1:1
	Anhydrite and gypsum screeds / Prefabricated screeds	1:2	1:1	Undiluted
	Existing smoothing compounds	1:3	1:2	Undiluted
	Adhesive residues	1:1	Undiluted	
	Wood	1:1	Undiluted	
	Mastic asphalt screeds	1:1	Undiluted	
	Ceramic, natural stones, terrazzo	1:1	Undiluted	
	Existing flooring	Undiluted		
	Adhesion promoter on epoxy or polyurethan Mapei primers	Undiluted		
	Priming before the application of Mapei silylated polymer-based adhesives for wood	Suitable, dilution based on the substrate	Suitable, dilution based on the substrate	
DRYING TIME	0 – 60 minutes, according to the use	30 – 60 minutes, according to the use	30 – 60 minutes, according to the use	
APPLICATION WITH				
EMICODE	EC1 Plus			
BLAUER ENGEL	DE-UZ 113	DE-UZ 113		
CONSUMPTION	Undiluted: approx 150 g/m ² Diluted 1:1: approx 75 g/m ² Diluted 1:2: approx. 50 g/m ² Diluted 1:3: ca. 35 g/m ² Diluted 1:4: ca. 30 g/m ²	Undiluted: approx 150 g/m ² Diluted 1:1: approx 75 g/m ² Diluted 1:2: approx 50 g/m ²	Undiluted: approx 150 g/m ² Diluted 1:1: approx 75 g/m ²	



MAPEI SpA
Via Cafiero, 22 - 20158 Milan (Italy)
Tel. +39-02-37673.1
mapei.com - mapei@mapei.it