







YOU NED LOCKING UP

A MORTAR'S POINT OF VIEW

"They say that I am seven times stronger than the concrete used to make pillars that hold up buildings. They say that I have formidable resistance to aggressive salts and freezing weather. This all makes me seem like matter from another planet; as if I were that stuff that melts and then recombines that you can see in the movie Terminator. But all I am is mortar; okay, I am Mapestone TFB 60 ultra high-strength supermortar, but I am still only mortar, something that locks stone together. And you'd better not forget it. Anyway, if the ancient Romans had been able to use me to build their roads, nobody else would have got a look in. They have used me on the Bobo (Bologna for Bologna) construction site to get the maximum cohesion possible between one flagstone and another in Strada Maggiore, and I can hear the antique flagstones now as they whisper: "you make everything look so simple, little mortar", "your masters don't work as well as the Romans", "they manage to get by thanks to you", end even "of course it was all so different in the good old days, shame on you, it's a sacrilege...". Nasty little flagstones, ungrateful masochists, don't you remember how badly those Roman chisels treated you, strike after strike, pushing one stone against the other, with just really tight, narrow joints to create a solid mass effect, forcing you to match as close as possible? Sand and river gravel were the weak points. The binder was the weak point. The Romans didn't have a really sound binder but, let's get to the point; the Italians are still the best in the world at constructing roads. And if today they can count on me, it means we have always been at the forefront, right back since ancient Roman times. The mallet blows will make you sink into the support of my cradle, my gums will rise up, the wheelbarrows will pour me into the gaps until they are filled, when the bonding slurry has dried out you will be tied to me forever, I will hold you tight in the heat and in the cold, in the rain and snow, even under the weight of the wheels of the trolleybuses and cars, from here you will never move again. I am a super-mortar because you need locking up."











MODERN ROAD SURFACES IN STONE

IN COMPLIANCE WITH UNI 11714-1:2018

The new UNI 11714-1:2018 standard introduces the classification of external paving according to the type of traffic loads and, for each class (P4, P5, P6, P7, P8 and P9), identifies the main design conditions.



PEDESTRIAN USE ONLY

Balconies, terraces, patios, courtyards, domestic paths and pavements



PEDESTRIAN AND LIGHT VEHICLE USE

Pavements suitable for parking, carparks or ramps/garage pathways, courtyards, adjacent lots and pathways for the connection between buildings and their parking lots



PEDESTRIAN AND LIGHT VEHICLE USE

Areas with a 30 km/h speed limit, streets or squares with limited access to vehicles, public carparks and public access ramps



PEDESTRIAN USE ONLY

External terraces of restaurants/bars, pavements for pedestrian and cycle use only



PEDESTRIAN AND LIGHT VEHICLE USE

Squares used occasionally by slow-moving vehicles, including heavy vehicles (parvises, cemeteries, etc.), market squares, loading/offloading areas, and squares for events, town festivals, etc.



HEAVY VEHICLE USE

Streets, streets with lanes for public transport or prescribed lanes, high-traffic roads, roundabouts and speed bumps





NEW

MAPESTONE GR-ECO

Architectural paving with filtering properties



MAPESTONE JOINT

Flexible and pervious paving



SISTEMA **MAPESTONE**

Monolithic waterproofing paving



SISTEMA MAPESTONE CALCIX

Architectural paving even of historical interest





MAPESTONE GR-ECO

Mapestone GR-ECO is a pre-blended, cement and lime-free grouting mortar made from natural fibres (apple fibres) and specific aggregates for grouting architectural stone, self-locking cementitious block, porcelain or terracotta brick paving subjected to light stresses and loads from pedestrians and light vehicles in classes P4, P5 and P6; complies with UNI 11714-1:2018.

Mapestone GR-ECO can be used to create architectural stone paving with filtering properties, and the binder component of Mapestone GR-ECO has self-generating properties: the fibres hold the water and then release it in the form of vapour, just like a sponge.









AREAS OF USE

Mapestone GR-ECO is used for filling grouts in architectural paving subjected to light loads, such as access areas to homes, hotels and carparks subjected to modest use by vehicles and for pedestrian zones, pavements and porticoes.

MAPESTONE GR-ECO AND SUSTAINABILITY

Thanks to its special formulation, Mapestone GR-ECO reduces the level of CO_2 emissions responsible for climate change by up to 95% compared with traditional slurry. For example, if used to renovate a piazza with an area of around 500 m², using Mapestone GR-ECO instead of traditional slurry saves almost 10,000 tonnes of CO_2 , the equivalent of 100 fewer car journeys from Milan to Rome or the planting of 130 trees.

Mapestone GR-ECO is a highly sustainable product, in that its reduced impact on the environment safeguards our planet and the absence of harmful substances quarantees the health of end users.





MAPESTONE GR-7

Mapestone GR-7 is a pre-blended, cement and lime-free mortar made from natural fibres (apple fibres), Pozzolan-reaction materials and specific aggregates for grouting architectural stone, self-locking cementitious block, porcelain or terracotta brick paving subjected to light stresses and loads from pedestrians and light vehicles in classes P4, P5 and P6; complies with UNI 11714-1:2018.

Thanks to its particular composition, its mechanical strength reaches 7 MPa which makes it particularly suitable for paving class P6.







LOOSE-BED INSTALLATION

MAPESTONE GR-ECO Porphyry binderi block Compacted 4/8 gravel, thickness 5 cm Ground

LOOSE-BED INSTALLATION WITH A BROADCAST OF CEMENT



INSTALLATION ON MAPESTONE TFB







THE CAUSES OF DETERIORATION











MECHANICAL STRESSES

The constant passage of cars and heavy vehicles generates compressive stress (the weight of the vehicles themselves) and tensile stress (manoeuvres carried out by vehicles) that cause failure in weak and irregular substrates on which the blocks of stone that make up the road surface have been installed.



FREEZE/THAW CYCLES, DE-ICING SALTS AND SEA-SALTS

There is a contrast between the high amount of heat generated when using de-icing salts (calcium and sodium chloride) and brusque cooling down due to low surrounding temperatures. This alternation in temperatures, combined with freeze/thaw cycles (with stresses caused by water cooling down and turning into ice), causes contraction, expansion and crumbling, which in turn deteriorate the joints and substrate. The action of chlorides in the sea-salts accelerates deterioration in porous cementitious matrixes.



DESIGN AND INSTALLATION

Modern stone road surfaces must be developed and then designed as structures that are meant TO LAST over the years, similar to any other vertical structure. With this in mind, choosing the most suitable installation system is fundamental. Also, using only expert workers qualified in the installation of stone is a key factor to ensure that this type of system is installed correctly. If unsuitable installation systems or methods are chosen, the service life of stone road surfaces will be shortened.









MAPEI SOLUTIONS





MAPESTONE JOINT

Mapestone Joint is a one-component, solvent-free, non-flammable, absorbing, polyurethane binder with a characteristic odour, used for grouting for flexible ioints and pervious architectural stone paving, particularly resistant to de-icing salts, to thermal shock and to acids; it allows opening to vehicular traffic in short times (48 hours after placing at +20° C). Mapestone Joint is available in 25 kg tanks, 200 kg drums and 1000 kg IBC containers.

Mapestone Joint Cleaner is the new specific cleaner and thinner for Mapestone Joint. It is used to remove resin residues that deposit on stone architectural paving during joint grouting made with Mapestone Joint. It is also efficient for cleaning the tools after Mapestone Joint application. It is preferable to use Mapestone Joint Cleaner before the residues harden. Mapestone Joint Cleaner is available in 5 I tanks.



Fill the grouts with **Mapestone Joint** resin



Clean product residues with **Mapestone Joint Cleaner**



Resin-grouted blocks



CROSS SECTION OF A BLOCK PAVING GROUTED WITH MAPESTONE JOINT

5/8 cm thick installation bed of 4/8 mm or 3/6 mm coarse stone chippings

3 Blocks of porphyry or other stone material



4 3/6 mm gravel infill



Mapestone Joint



TECHNICAL ADVANTAGES

- FLEXIBLE SYSTEM
- PERVIOUS CAPACITY
- RESISTANT TO FREEZING WEATHER, DE-ICING SALTS, SEA-SALTS AND SEA SPRAY

ECONOMIC ADVANTAGES

- HIGHLY DURABLE FINISHED WORK
- HIGH RESISTANCE TO THE CLEANING ACTION OF **POWER SWEEPERS**
- NO WASTE OF MATERIAL
- LESS TIME REQUIRED FOR ROAD WORKS

SOCIAL ADVANTAGES

- LOWER MAINTENANCE COSTS
- LESS NOISE
- LESS DISRUPTION FOR **INHABITANTS**
- FEWER ACCIDENTS (DUE TO FALLS FROM BIKES, MOPEDS AND HIGH HEELS)







System to create elastic and pervious architectural stone paving by applying **Mapestone Joint**. For use with **block**, **sett** and **pebble** paving in class P4, P5, P6, P7, P8 and P9.





Install the stone blocks on a bed of 4/8 mm or 3/6 mm coarse stone chippings



After wetting the surface, use a vibrating plate compactor



Fill the grout lines with 3/6 mm stone chippings



Fill the grout lines with **Mapestone Joint**





System to create elastic and pervious architectural stone paving by applying **Mapestone Joint**. For use with **slab** paving in class P4, P5 and P6.



Prepare and apply the mix made up of 3/6 mm coarse stone chippings and **Mapestone Joint**




Apply **Mapestone Joint** on the back of the slabs



Install and tap down the slabs



Fill the grouts with 3/6 mm coarse stone chippings and **Mapstone Joint**





MAPEI SOLUTIONS






MAPESTONE SYSTEM



The monolithic **Mapestone System** represents "turnkey" а solution with UNI 11714-1:2018 compliance standard to obtain durable, long-lasting work resistant to freeze-thaw cycles, de-icing salts and to sea water. Mapei has specifically developed pre-blended cementitious products with exceptional physical-chemical characteristics suitable for areas exposed cyclically to wet and dry periods, as described in exposure class XF4 cementitious products which need only to be mixed with water, made from special binders and selected aggregates, to make architectonic stone paving which is suitable for vehicles. The System includes: Mapestone TFB 60, a pre-blended powder mortar, particularly suitable for making screeds and installing stone; Mapestone PFS, Mapestone PFS 2 Flex, Mapestone PFS 2 Visco and Mapestone PFS PCC 2, pre-blended powder mortars for grouting joints. The combined use of these products creates a long-lasting monolithic structure.










- Concrete
- Non-woven fabric or PVC sheets
- Mapestone TFB 60

- Porphyry and flagstones
 Mapestone PFS 2 or Map Mapestone PFS 2 or Mapestone PFS 2 Flex or Mapestone PFS 2 Visco or Mapestone PFS PCC 2







MAPESTONE SYSTEM





SAFETY Prevents wear and tear, often the cause

of accidents.




DURABILITY Withstands the rigours of the most intense road traffic.

WHERE TO USE

The monolithic **Mapestone System** is used to make architectural stone paving (made from setts, smolleri, pebbles, slabs and blocks).

When it is not necessary to meet the requirements for exposure classes XF3, XF4 and XS3, joints may be quickly grouted with **Keracolor PPN**.




Paving stones






Pebbles



Blocks



Low-thickness slabs















TECHNICAL ADVANTAGES

- HIGH MECHANICAL STRENGTH
- HOMOGENOUS, UNIFORM PRODUCT
- RESISTANT TO FREEZING WEATHER AND DE-ICING SALTS
- RESISTANT TO SEA SALTS, THAT MEANS DURABLE, LONG-LASTING WORK

LOGISTIC ADVANTAGES


- REDUCTION IN AMOUNT OF WASTE AND OBSTACLES DUE TO ROAD-WORKS
- LOW IMPACT ON THE ENVIRONMENT
- EASY TO CLEAN

SOCIAL ADVANTAGES

- LOWER MAINTENANCE COSTS
- LESS NOISE
- LESS DISRUPTION FOR INHABITANTS
- FEWER ACCIDENTS (DUE TO FALLS FROM BIKES, MOPEDS AND HIGH HEELS)

ECONOMIC ADVANTAGES

- HIGHLY DURABLE FINISHED WORK
- REDUCTION IN MAINTENANCE AND/OR REPAIR WORKS
- NO WASTE OF MATERIAL
- LESS TIME REQUIRED FOR ROAD WORKS





Colours available for **Mapestone PFS 2**, **Mapestone PFS 2 Flex** and **Mapestone PFS 2 Visco**

Due to the printing processes involved, the colours should be taken as merely indicative of the shades of the actual products





MAPEI SOLUTIONS





MAPESTONE CALCIX SYSTEM





Pre-blended mortars for screeds and grouting, made from natural hydraulic (NHL), inorganic Pozzolanic lime materials rich in amorphous silica, selected aggregates and specific additives for laying stone paving in areas subject to high pedestrian and light traffic; class P4, P5, P6 and P7 according to UNI 11714-1:2018, with good mechanical strength and resistance to frost. The system is made up of Mapestone TFB Calcix bedding screed for stones and grouting mortars Mapestone PFS Calcix (light colour) and Mapestone PFS Tenebris (dark colour), for their grouting. The combined use of the products makes it possible to realise architectural pavements NOT subject to heavy traffic, in squares, roads and sidewalks in Old Towns present in our countries and cities. The system is ideal for laying pebbles, blocks, smolleri and low-thickness slabs.











MAPESTONE CALCIX AND SUSTAINABILITY

The high percentage of recycled material allows **Calcix** products to contribute to CAM national sustainability protocols (MEC – Minimum Environmental Criteria) and international protocols such as LEED and BREEAM. The special formulation of the products allows the reduction of greenhouse gas emissions and a lower consumption of mineral resources, while maintaining durability and quality performances intact.













TECHNICAL ADVANTAGES

- GOOD MECHANICAL STRENGTH
- HOMOGENOUS, UNIFORM PRODUCT
- RESISTANT TO FREEZING WEATHER AND DE-ICING SALTS
- GOOD ADHESION TO STONE MATERIAL

LOGISTIC ADVANTAGES

- LOW IMPACT ON THE ENVIRONMENT
- EASY TO CLEAN

SOCIAL ADVANTAGES

- LOWER MAINTENANCE COSTS
- LESS NOISE
- FEWER ACCIDENTS (DUE TO FALLS FROM BIKES, MOPEDS AND HIGH HEELS)
- SUSTAINABLE PRODUCT, THANKS TO ITS SPECIAL FORMULATION

ECONOMIC ADVANTAGES

- HIGHLY DURABLE FINISHED WORK
- REDUCTION IN MAINTENANCE AND/OR REPAIR WORKS
- NO WASTE OF MATERIAL
- LESS TIME REQUIRED FOR ROAD WORKS



SOME WORKS CARRIED OUT WITH MAPESTONE SYSTEM

Via Aquileia, Udine (Italy)





San Giovanni in Persiceto (Italy)





Assisi (Italy)





















Parisian Hotel, Macau (China)






Largo Magnanapoli Rome (Italy)





Hôtel de Ville Vincennes, Paris (France)

Piazza Palazzo del Cinema, Lido di Venezia (Italy)







Via De' Cerretani Florence (Italy)



Piazza Unità d'Italia, Tradate (Italy)



EVERYTHING'S OK, WITH MAPEL

HEAD OFFICE MAPEI S.p.A. Via Cafiero, 22 20158 Milan +39-02-37673.1 mapei.com mapei@mapei.it

