

Keraquick Maxi S1

PRODUCTS FOR CERAMICS AND STONE MATERIAL

THE HIGH PERFORMANCE
RAPID-SETTING ADHESIVE



Keraquick Maxi S1



Keraquick Maxi S1, grey or white high performance, deformable, non-slip, rapid-setting and hydrating cementitious adhesive. Class C2FTS1 according to EN 12004 standard, ideal for installing ceramic tiles and particularly recommended for stone, including large and thick slabs.



KERAQUICK MAXI S1

THE HIGH PERFORMANCE RAPID-SETTING ADHESIVE

WHY CHOOSE KERAQUICK MAXI S1?




Extended workability: mix remains workable for 45 minutes.



Low viscosity mix for **easy, quick application.**



Highly thixotropic: may be applied on vertical surfaces without slumping and without allowing tiles to slip, including large, heavy formats.



Deformable (class S1): excellent capacity to absorb deformations in substrates and tiles.



Suitable for application in layers up to 15 mm thick: prevents large, heavy floor tiles from sinking when installed on thick layers of adhesive.




Rapid-setting and ready for use very quickly: floors may be opened to pedestrian use after just 3 hours and to traffic after just 24 hours



White version with **high white balance.**



Contains 5% of recycled materials.



Very low emission of VOC (volatile organic compounds) and certified EC1 R Plus by GEV.



Its impact on the environment during the entire life cycle has been measured using the **LCA** (Life Cycle Assessment) **method** and **results documented in product EPD** (Environmental Product Declaration) N° SP-01108.



Contributes to attaining **2 LEED credits** (Leadership in Energy and Environmental Design).

HEADQUARTERS

MAPEI SpA

Via Cafiero, 22 - 20158 Milan

Tel. +39-02-37673.1

Fax +39-02-37673.214

Internet: www.mapei.com

E-mail: mapei@mapei.it

