

MAPEFILL ZERO

Expansive fluid mortar for anchoring



Mapefill ZERO

DESCRIPTION

Fluid mortar with positive internal tension

Pre-blended powdered mortar composed of high-strength cement, graded aggregates and special admixtures. The product has excellent fatigue behaviour, which gives repaired structures a high level of resistance to cracking, including when subject to dynamic loads induced during normal service conditions. Suitable for precision anchoring of machinery or metallic structures and repairing damaged structures.



CO₂ FULLY OFFSET PRODUCT



CO₂ emissions measured throughout the life cycle of products from the **ZERO Line** in 2024 using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset through the acquisition of certified carbon credits in support of forestry protection projects.

A commitment to the planet, to people and to biodiversity. For more details on how emissions are calculated and on climate mitigation projects financed through certified carbon credits, visit the webpage ZERO.mapei.com.

Building a SUSTAINABLE future together

WHERE TO USE





10 mm 100 mm Thickness

procedure

CHARACTERISTICS



High fluidity



Excellent adhesion

Resistance to dynamic/

CERTIFICATIONS







PACKAGING 25 kg bag

CONSUMPTION 2 kg/dm³ of cavity to be filled

CHECK THE TECHNICAL DATA SHEET on mapei.com







EVERYTHING'S **OK**, WITH **MAPEI**



HEAD OFFICE MAPEI SpA Via Cafiero, 22 20158 Milan Tel. +39-02-37673.1 mapei.com mapei@mapei.it