



PLANITOP SMOOTH & REPAIR ZERO PLANITOP SMOOTH & REPAIR R4 ZERO

New **repairing** and **skimming** mortars



**NEW
FORMULA**





To meet the needs of installers, the formulation of **PLANITOP SMOOTH & REPAIR ZERO** and **PLANITOP SMOOTH & REPAIR R4 ZERO** cementitious repair mortars has been further improved to achieve the following advantages:

- ▶ **Improved** consistency
- ▶ **Improved** bonding during application
- ▶ **Easier** to build up at high thicknesses



CO₂ emissions measured throughout the life cycle of products from the **ZERO line** in 2024 using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset through the acquisition of certified carbon credits in support of forestry protection projects. A commitment to the planet, to people, and to biodiversity. For more details on how emissions are calculated and on climate mitigation projects financed through certified carbon credits, visit [ZERO.mapei.com](https://www.zero.mapei.com).

Planitop Smooth & Repair ZERO

DESCRIPTION

Quick-setting, R2-class, thixotropic, fine-grained cementitious mortar

Ideal for non-structural repairs and skimming internal and external, horizontal and vertical concrete surfaces.

Suitable for repairing structures exposed to the air and in permanent contact with water.



USE



Application procedure

approx. 15 Mins



Pot life



Thickness

PACKAGING

25 kg bags and boxes containing 4 x 5 kg packets.

CONSUMPTION

Approximately 16.5 kg/m² per cm of thickness.


CHARACTERISTICS



2 products in 1



Applicable at low thickness



Natural fine-grained finish



CERTIFICATIONS



Planitop Smooth & Repair R4 ZERO

DESCRIPTION

Structural R4-class, quick-setting, thixotropic, fine-grained cementitious mortar

Suitable for structural repairs and skimming internal and external horizontal and vertical concrete surfaces.

Suitable for repairing structures exposed to the air and in permanent contact with water.



USE



Application procedure

approx. **15 Mins**
+20°C



Pot life

from **3 mm** to **40 mm**



Thickness

PACKAGING
25 kg bags.

CONSUMPTION
Approximately 17 kg/m² per cm of thickness.


CHARACTERISTICS



2 products in 1



Applicable at low thickness



Structural restoration



CERTIFICATIONS



EVERYTHING'S OK WITH MAPEI



HEAD OFFICE
MAPEI SpA
Via Cafiero, 22
20158 Milan
+39-02-37673.1
mapei@mapei.it
mapei.com