Declaration of performance: No. CPR-IT1/0012

- 1. Unique identification code of the product-type: **ANTIPLUVIOL S**
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR **SURFACE PROTECTION PRODUCT HYDROPHOBIC IMPREGNATION**
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
 Hydrophobic impregnation for intended use in concrete surface protection by protection against ingress; moisture control and increasing resistivity methods
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): MAPEI S.p.A. – Via Cafiero, 22 – Milano (Italy) www.mapei.it
- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 2+
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body ICMQ S.p.A., No. 1305, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificate of conformity of the factory production control no. 1305-CPD-0616.

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**

Essential characteristics	Performance	Harmonised technical specification	
Depth of penetration:	Class I: < 10		
Water absorption and resistance to alkali as:	mm		
 absorption ratio compared with the untreated specimen: 		EN 1504-2:2004	
- absorption ratio after immersion in alkali	< 7,5 %		
solution:	< 10 %		
Drying rate for hydrophobic impregnation:	Class I: > 30 %		
Dangerous substances:	NPD		

9. Declared performance:

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Paolo Murelli** – **Corporate Quality Management**

(name and function)



CE MARKING according to CPR 305/2011 and EN 1504-2:2004

CE 1305	Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it		
	09		
	CPR-IT1/0012		
EN 1504-2:2004			
	ANTIPLUVIOL S		
Hydrophobic impregnation product for intended use in concrete surface protection by protection against ingress; moisture control and increasing resistivity methods			
Depth of penet Water absorption	ration: on and resistance to alkali as:	Class I: < 10 mm	
- absorption r	atio compared with the untreated specimen:	< 7,5 %	
	atio after immersion in alkali solution:	< 10 %	
Drying rate for Dangerous sub	hydrophobic impregnation: stances:	Class I: > 30 % NPD	