

Safety Data Sheet

MAPECOAT FINISH TS / B

Safety Data Sheet dated: 04/02/2020 - version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MAPECOAT FINISH TS / B

Trade code: 9025183

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Polyurethanic coating

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel: +39-02-376731

Fax: +39-02-37673.214

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

MAPEI S.p.A. - Tel. +(39)02376731 - (office hours)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3 Flammable liquid and vapour.

Acute Tox. 4 Harmful if inhaled.

Skin Sens. 1 May cause an allergic skin reaction.

STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor/... if you feel unwell.

P321 Specific treatment (see ... on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use ... to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to

Special Provisions:

EUH208 Contains 4-isocyanatesulphonyltoluene;-tosyl isocyanate. May produce an allergic reaction.

Contains:

Hexamethylene diisocyanate, oligomers

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT/vPvB Ingredients are present

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: MAPECOAT FINISH TS / B

Hazardous components within the meaning of the CLP regulation and related classification:

Quantity	Name	Ident. Numb.	Classification	Registration Number
≥50 - <75 %	Hexamethylene diisocyanate, oligomers	CAS:28182-81-2 EC:500-060-2	Acute Tox. 4, H332; STOT SE 3, H335; Skin Sens. 1, H317	01-2119970543-34-XXXX
≥25 - <50 %	2-methoxy-1-methylethyl acetate	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226	01-2119475791-29-xxxx
≥0.1 - <0.25 %	4-isocyanatesulphonyltoluene;-tosyl isocyanate	CAS:4083-64-1 EC:223-810-8 Index:615-012-00-7	Eye Irrit. 2, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1,1A,1B, H334, EUH014	01-2119980050-47-XXXX
<0.0015 %	chlorobenzene	CAS:108-90-7 EC:203-628-5 Index:602-033-00-1	Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Aquatic Chronic 2, H411	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.
Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.
In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
2-methoxy-1-methylethyl acetate	ACGIH	NNN		275	50	550	100		Skin
	SUVA	NNN		275	50				
	National	SWEDEN		250	50	400	75		SWEDEN, Short-term value, 15 minutes average value
	National	FINLAND		270	50	550	100		FINLAND, hud
	National	NORWAY		270	50				NORWAY, H
	NDS	NNN		260					
	NDSch	NNN		520					
	EU	NNN		275	50	550	100		Skin
	National	NORWAY		275	50	550	100		
	DFG	GERMANY	C			270	50		
	National	SWEDEN		275	50				
	National	FRANCE		275	50	550	100		
	National	SPAIN		275	50	550	100		
	National	GREECE		275	50	550	100		
	National	DENMARK		275	50				
	National	FINLAND		270	50	550	100		
	National	GERMANY		270	50				
	National	PORTUGAL		275	50	550	100		
	National	NORWAY		270	50	337,5	75		
	National	BELGIUM		275	50	550	100		
	NDS	POLAND		260					
	NDSch	POLAND				520			
	CHE	SWITZERLAND				275	50		
	NDS	NETHERLANDS		550					
	National	CZECHIA		270					
	National	HUNGARY		275		550			
	National	ESTONIA		275	50	550	100		
	National	LATVIA		275	50	550	100		
	National	CZECHIA	C			550			
	National	SLOVAKIA	C			550			
	National	SLOVAKIA		275	50				
	National	SLOVENIA		275	50	550	100		
	National	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND		274	50	548	100		
	National	BULGARIA		275,0	50	550,0	100		
	National	ROMANIA		275	50	550	100		
	TUR	TURKEY		275	50	550	100		

	National LITHUANIA	250	50	400	75		
	National CROATIA	275	50	550	100		
	EU	275	50	550	100	Indicative	Possibility of significant uptake through the skin
4-isocyanatesulphonyltoluene;-tosyl isocyanate	SUVA NNN	0,020		0,020			
chlorobenzene	National SWEDEN	23	5	70	15		SWEDEN, Short-term value, 15 minutes average value
	National FINLAND	23	5	70	15		FINLAND, hud
	National NORWAY	23	5				
	National FINLAND	23	5	70	15		FINLAND, hud
	National NORWAY	46	10	92	20		
	National POLAND	23		70			
	DFG GERMANY C			46	10		
	ACGIH		10				A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;liver damage
	National SWEDEN	23	5				
	EU	23	5	70	15	Indicative	
	National FRANCE	23	5	70	15		
	National SPAIN	23	5	70	15		
	National GREECE	23	5	70	15		
	National DENMARK	23	5				
	National FINLAND	23	5	70	15		
	National GERMANY	23	5				
	National PORTUGAL	23	5	70	15		
	National NORWAY	23	5	34,5	10		
	National BELGIUM	23	5	70	15		
	NDS POLAND	23					
	NDSch POLAND			70			
	CHE SWITZERLAND			92	20		
	NDS NETHERLANDS	23		70			
	National CZECHIA	25					
	National HUNGARY	23		70			
	Malaysia MALAYSIA a OEL	46	10				
	National ESTONIA	23	5	70	15		
	National LATVIA	23	5	70	15		
	National CZECHIA C			70			
	National SLOVAKIA C			70			
	National SLOVAKIA	23	5				

National SLOVENIA	23	5	69	15
National UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4,7	1	14	3
National BULGARIA	23,0	5	70,0	15
National ROMANIA	23	5	70	15
TUR TURKEY	23	5	70	15
National LITHUANIA	23	5	70	15
National CROATIA	23	5	70	15

Biological Exposure Index

CAS-No.	Component	Value	UoM	Medium	Biological Indicator	Sampling Period
108-90-7	chlorobenzene	100	MGGCREAT	Urine	Clorocatecolo	End of turn; End of working week
		20	MGGCREAT	Urine	P-chlorophenol	End of turn; End of working week

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC LIMIT	Exposure Route	Exposure Frequency	Remark
Hexamethylene diisocyanate, oligomers	28182-81-2	0,127 mg/l	Fresh Water		
		0,0127 mg/l	Marine water		
		53182 mg/kg	Soil		
		266700 mg/kg	Freshwater sediments		
		26670 mg/kg	Marine water sediments		
		38,3 mg/l	Microorganisms in sewage treatments		
2-methoxy-1-methylethyl acetate	108-65-6	1,27 mg/l	Intermittent release		
		0,635 mg/l	Fresh Water		
		0,0635 mg/l	Marine water		
		3,29 mg/kg	Freshwater sediments		
		0,329 mg/kg	Marine water sediments		
		6,35 mg/l	Intermittent release		
		100 mg/l	Microorganisms in sewage treatments		
		0,29 mg/kg	Soil		

Derived No Effect Level. (DNEL)

Component	CAS-No.	Worker Industrial	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
Hexamethylene diisocyanate, oligomers	28182-81-2	1 mg/m3			Human Inhalation	Short Term, local effects	

		0,5 mg/m3		Human Inhalation	Long Term, local effects
2-methoxy-1- methylethyl acetate	108-65-6	796 mg/kg	320 mg/kg	Human Dermal	Long Term, systemic effects
		275 mg/m3	33 mg/m3	Human Inhalation	Long Term, systemic effects
			36 mg/kg	Human Oral	Long Term, systemic effects
		550 mg/m3		Human Inhalation	Short Term, local effects

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Use adequate protective respiratory equipment.

Hygienic and Technical measures

N.A.

Appropriate engineering controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour: Liquid transparent

Odour: characteristic

Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 146 °C (295 °F)

Flash point: N.A.

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: N.A.

Solubility in water: N.A.

Partition coefficient (n-octanol/water): N.A. - This product is a mixture

Auto-ignition temperature: N.A. - No explosive or spontaneous ignition in contact with air at room temperature

Decomposition temperature: N.A.

Viscosity: 700.00 cPs

Explosive properties: N.A. - No components with explosive properties

Oxidizing properties: N.A. - No component with oxidizing properties

Solid/gas flammability: N.A.

9.2. Other information

No additional information

SECTION 10: Stability and reactivity

10.1. Reactivity

It may generate dangerous reactions (See subsections below)

10.2. Chemical stability

It may generate dangerous reactions (See subsections below)

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid accumulating electrostatic charge.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

Hexamethylene diisocyanate, oligomers	a) acute toxicity	LD50 Oral Rat > 2500 mg/kg	ratto femmina
		LD50 Skin Rat > 2000 mg/kg	
		LD50 Skin Rabbit > 2000 mg/kg	
		LC50 Inhalation Mist Rat = 0,390 mg/l 4h	ratto femmina
		LC50 Inhalation Rat = 18500 mg/m ³ 1h	
2-methoxy-1-methylethyl acetate	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg	
		LD50 Skin Rabbit > 5000 mg/kg	
		LC50 Inhalation Dust Rat > 23,8 mg/l	
		LD50 Skin Rabbit > 5 g/kg	
		LD50 Oral Rat = 8532 mg/kg	
	e) germ cell mutagenicity	NOAEL Inhalation Rat = 1000 ppm	
	g) reproductive toxicity	NOAEL Inhalation Rat = 500 ppm	
4-isocyanatesulphonyltoluene;-tosyl isocyanate	a) acute toxicity	LC50 Inhalation Rat > 640 ppm 1h	
		LD50 Oral Rat = 2234 mg/kg	
chlorobenzene	a) acute toxicity	LD50 Oral Rat 2000 mg/kg	
		LD50 Skin Rabbit > 7940 mg/kg	
		LC50 Inhalation Rat = 13,5 mg/l 7h	

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- k) Toxicological kinetics, metabolism and distribution information
- i) STOT-repeated exposure

SECTION 12: Ecological information**12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
Hexamethylene diisocyanate, oligomers	CAS: 28182-81-2 - EINECS: 500-060-2	a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia > 100 mg/L 48 a) Aquatic acute toxicity : EC50 Algae > 1000 mg/L 72 c) Bacteria toxicity : EC50 Bacteria = 3828 mg/L 3
2-methoxy-1-methylethyl acetate	CAS: 108-65-6 - EINECS: 203-603-9 - INDEX: 607-195-00-7	a) Aquatic acute toxicity : LC50 Fish = mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia > 500 mg/L 48 b) Aquatic chronic toxicity : NOEC Fish = 47,5 mg/L - 14 d b) Aquatic chronic toxicity : NOEC Daphnia = 100 mg/L - 21 d a) Aquatic acute toxicity : EC50 Algae > 1000 mg/L 72 a) Aquatic acute toxicity : NOEC Algae = 1000 mg/L 96 a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 161 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna > 500 mg/L 48h IUCLID
chlorobenzene	CAS: 108-90-7 - EINECS: 203-628-5 - INDEX: 602-033-00-1	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 7 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio = 91 mg/L 96h IUCLID d) Terrestrial toxicity : LC50 Worm Eisenia foetida = 29 mg/cm2 48h IUCLID a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 4,5 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 6,9 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 4,1 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 4,1 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 36,35 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 0,59 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 2,55 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 12,5 mg/L 96h EPA

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6. Other adverse effects

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Product:

Do not dispose of waste into sewers.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to an authorized waste disposal service.

Contaminated packaging:

Empty remaining content.

Dispose of as unused product.

Do not re-use empty containers.

SECTION 14: Transport information**14.1. UN number**

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT or PAINT RELATED MATERIAL

IATA-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 3

ADR-Hazard identification number: -

ADR-Special Provisions: 163 367 650

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 355

IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3 A72 A192

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 163 223 367 955

IMDG-EMS: F-E, S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC) : 430 (A+B) g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) 2015/830

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
Products belongs to category P5c	5000	50000

German Water Hazard Class

N.A.

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 30

SVHC Substances:

No Data Available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
EUH014	Reacts violently with water.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.1/1-1A-1B	Resp. Sens. 1,1A,1B	Respiratory Sensitisation, Category 1,1A,1B
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008

[CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
--	---------------------------------

2.6/3	On basis of test data
3.1/4/Inhal	Calculation method
3.4.2/1	Calculation method
3.8/3	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 5. FIRE-FIGHTING MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 13. DISPOSAL CONSIDERATIONS
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION