

## Declaration of performance: No. CPR-IT1/0284

1. Unique identification code of the product-type: **PLANIGROUT 300**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

### **ANCHORING THREE-COMPONENT EPOXY MORTAR FOR STRENGTHENING CONCRETE**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**strengthening concrete by installing reinforcing steel (rebars)  
in buildings and civil engineering works**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI S.p.A. – Via Cafiero, 22 – Milano (Italy)** **www.mapei.it**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 2+**  
**System 3 for reaction to fire**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The notified body ICMQ S.p.A., No. 1305, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificate of conformity of the factory production control No. 1305-CPD-0616.**

**The notified testing laboratory CSI S.p.A., N. 0497, performed the determination of the class of reaction to fire on samples taken by the manufacturer, under system 3, and issued the report No. DC01/CL/078F08.**

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance


Essential characteristics	Performance	Harmonised technical specification
<b>Pull-out displacement:</b>	<b>≤ 0,6 mm at load of 75 kN</b>	<b>EN 1504-6:2006</b>
<b>Chloride ion content:</b>	<b>≤ 0,05 %</b>	
<b>Glass transition temperature:</b>	<b>≥ 45° C</b>	
<b>Reaction to fire:</b>	<b>Class D-s2,d2</b>	
<b>Creep under tensile load displacement:</b>	<b>≤ 0,6 mm after continuous loading of 50 kN for 3 months</b>	
<b>Dangerous substances:</b>	<b>see SDS</b>	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**  
(name and function)

**Milan, 01/07/2013**  
(place and date of issue)

  
.....  
(signature)

## CE MARKING according to CPR 305/2011 and EN 1504-6:2006

 1305, 0497	 Via Cafiero, 22 – 20158 Milano (Italy) <a href="http://www.mapei.it">www.mapei.it</a>												
<p style="text-align: center;"><b>09</b> <b>CPR-IT1/0284</b> <b>EN 1504-6:2006</b> <b>PLANIGROUT 300</b> <i>Anchoring product for strengthening concrete by installing reinforcing steel (rebars)</i></p> <table><tr><td>Pull-out displacement:</td><td>≤ 0,6 mm at load of 75 kN</td></tr><tr><td>Chloride ion content:</td><td>≤ 0,05 %</td></tr><tr><td>Glass transition temperature:</td><td>≥ 45° C</td></tr><tr><td>Reaction to fire:</td><td>Class D-s2,d2</td></tr><tr><td>Creep under tensile load displacement:</td><td>≤ 0,6 mm after continuous loading of 50 kN for 3 months</td></tr><tr><td>Dangerous substances:</td><td>see SDS</td></tr></table>		Pull-out displacement:	≤ 0,6 mm at load of 75 kN	Chloride ion content:	≤ 0,05 %	Glass transition temperature:	≥ 45° C	Reaction to fire:	Class D-s2,d2	Creep under tensile load displacement:	≤ 0,6 mm after continuous loading of 50 kN for 3 months	Dangerous substances:	see SDS
Pull-out displacement:	≤ 0,6 mm at load of 75 kN												
Chloride ion content:	≤ 0,05 %												
Glass transition temperature:	≥ 45° C												
Reaction to fire:	Class D-s2,d2												
Creep under tensile load displacement:	≤ 0,6 mm after continuous loading of 50 kN for 3 months												
Dangerous substances:	see SDS												