

DECLARATION OF PERFORMANCE N. CPR-IT1/0457

- 1) Unique identification code of the product type: **MAPESIL BM**
- 2) Intended uses: **silicone sealant for non-structural internal and external use in façade elements, glazing application and pedestrian walkways, also in cold climates.**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 3**
- 5) Harmonised standards: **EN 15651-1:2012, EN 15651-2:2012, EN 15651-4:2012**

Notified bodies:

The notified laboratory SKZ-TeConA GmbH, N. 1213, carried out the assessment of the performance on the basis of testing on samples taken by the manufacturer.

- 6) Declared performances:

EN 15651-1:2012 F-EXT-INT-CC (CLASS 25LM)
Conditioning: Method A
Substrate: Glass and aluminium without primer
Mortar M1 with PRIMER G 783

Essential characteristics	Performances
Reaction to fire	Class E
Release of dangerous substances	See SDS
Water tightness and air tightness:	
– Resistance to flow	≤ 2 mm
– Loss of volume	≤ 10 %
– Tensile properties at maintained extension after immersion in water	Pass
– Secant tensile modulus at -30°C	≤ 0,9 MPa
– Tensile properties at maintained extension at -30°C	Pass
Durability	Pass

EN 15651-2:2012 G-CC (CLASS 25LM)
Conditioning: Method A
Substrate: Glass and aluminium without primer

Essential characteristics	Performances
Reaction to fire	Class E
Release of dangerous substances	See SDS
Water tightness and air tightness:	
– Resistance to flow	≤ 2 mm
– Loss of volume	≤ 10 %
– Adhesion and cohesion properties after exposure to artificial light	Pass
– Elastic recovery	≥ 70 %
– Secant tensile modulus at -30°C	≤ 0,9 MPa
– Tensile properties at maintained extension at -30°C	Pass
Durability	Pass

EN 15651-4:2012

PW-EXT-INT-CC

(CLASS 25LM)

Conditioning:

method A

Substrate:

Glass and aluminium without primer

Mortar M1 with PRIMER G 783


Essential characteristics	Performances
Reaction to fire	Class E
Release of dangerous substances	See SDS
Water tightness and air tightness:	
– Tensile properties at maintained extension	Pass
– Loss of volume	≤ 10 %
– Tear resistance	Pass
– Adhesion and cohesion properties at maintained extension after immersion in water	Pass
– Adhesion and cohesion properties at maintained extension after immersion in salt water	Pass
– Secant tensile modulus at -30°C	≤ 0,9 MPa
– Tensile properties at maintained extension -30°C	Pass
Durability	Pass

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

In **Milan, 01/07/2014**



DoP in Pdf format are available in the Mapei website

Revision notes: first release of the current document