

Safety Data Sheet

PRIMER FD

Safety Data Sheet dated: 5/3/2019 - version 1



Section 1. Identification of the substance and supplier

Product identifier

Mixture identification:

Trade name: PRIMER FD

Trade code: 019152

Recommended use of the chemical and restrictions on use

Recommended use: Solvent-borne primer

Uses advised against: N.A.

Supplier's details

Company: MBP (NZ) Ltd. - 88 Carbine Road, Mount Wellington, Auckland 1060, New Zealand Email: enquiries@MBPLtd.co.nz

Website: www.MBPLtd.co.nz - Phone: +64 9 921 1994 (Mon-Fri 9am-5pm) - Fax: +64 9 921 1993

Emergency phone number

New Zealand Poisons Centre: Ph: 0800 764 766

Section 2. Hazards identification

HSNO hazard classification

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2017.

HSNO classification:

- | | |
|--------------------------|---|
| 3.1B | H225 - Highly flammable liquid and vapour. |
| 6.3A | H315 - Causes skin irritation. |
| 6.4A | H319 - Causes serious eye irritation. |
| 6.8B | H361.G - Suspected of damaging fertility or the unborn child if inhaled, in contact with skin and if swallowed. |
| 6.9B (narcotic effects) | H336 - May cause drowsiness or dizziness. |
| 6.9B (Repeated exposure) | H373.G - May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed. |
| 6.1E (aspiration) | H304 - May be fatal if swallowed and enters airways. |

Hazard information

Pictograms and Signal Words



Danger

Hazard statements:

- | | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361 | Suspected of damaging fertility or the unborn child if inhaled, in contact with skin and if swallowed. |
| H373 | May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed. |

Precautionary statements:

- | | |
|------|---|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. — No smoking. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |

P260	Do not breathe mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see supplementary instructions on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use a dry powder fire extinguisher for extinction.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Other hazards which do not result in a classification

No other hazards

Section 3. Composition/information on ingredients

Substances

N.A.

Mixtures

Mixture identification: PRIMER FD

Hazardous components within the meaning of HSNO Act and related classification

Quantity	Name	Ident. Numb.	Classification
≥50 - <75 %	acetone; propan-2-one; propanone	CAS:67-64-1 EC:200-662-2 Index:606-001-00-8	3.1B, H225; 6.4A, H319; 6.9B (narcotic effects), H336
≥10 - <20 %	toluene	CAS:108-88-3 EC:203-625-9 Index:601-021-00-3	3.1B, H225; 6.3A, H315; 6.8B, H361d; 6.9B (narcotic effects), H336; 6.9B (Repeated exposure), H373; 6.1E (aspiration), H304

Section 4. First aid measures

Description of necessary first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

In case of fire: Use a dry powder fire extinguisher for extinction.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: 2.3%-13.0%

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Methods and materials for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Section 7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Section 8. Exposure controls/personal protection

Workplace Exposure Standards

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
acetone; propan-2-one; propanone	NZL	NEW ZEALAND		1185	500	2375	1000		
toluene	NZL	NEW ZEALAND		188	50				

Biological Exposure Index

CAS-No.	Component	Value	UoM	Medium	Biological Indicator	Sampling Period
67-64-1	acetone; propan-2-one; propanone	25	mg/L	Urine	Acetone	End of turn
108-88-3	toluene	0,02	mg/L	Blood	Toluene	Before last turn of the working week
		0,03	mg/L	Urine	Toluene	End of turn
		0,3	MGGCREAT	Urine	O-Cresol	End of turn

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC LIMIT	Exposure Route	Exposure Frequency	Remark
acetone; propan-2-one; propanone	67-64-1	30,4	Freshwater sediments		
		3,04	Marine water sediments		
		10,6	Fresh Water		
		1,06	Marine water		
		29,5	Soil		
		100	Microorganisms in sewage treatments		
toluene	108-88-3	16,39	Freshwater sediments		PNEC
		2,31	Soil		PNEC
		16,39	Marine water sediments		PNEC
		0,68	Fresh Water		PNEC
		0,68	Marine water		PNEC
		0,68	Intermittent release		PNEC
		6,58	Microorganisms in sewage treatments		

Derived No Effect Level. (DNEL)

Date 5/3/2019 Production Name PRIMER FD

Page n. 4 of 10

Component	CAS-No.	Worker Industrial	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark	
acetone; propan-2-one; propanone	67-64-1	186			Human Dermal	Long Term, systemic effects		
		2420			Human Inhalation	Short Term, systemic effects		
		1210			Human Inhalation	Long Term, systemic effects		
			62			Human Oral	Long Term, systemic effects	
			62			Human Dermal	Long Term, systemic effects	
			200			Human Inhalation	Long Term, systemic effects	
toluene	108-88-3	2420			Human Inhalation	Short Term, local effects		
		384		226	Human Dermal	Long Term, systemic effects		
		192		56,5	Human Inhalation	Long Term, systemic effects		
			8,13		Human Oral	Long Term, systemic effects		
		226			Human Dermal	Long Term, systemic effects		

Engineering Controls

N.A.

Personal Protective Equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

N.A.

Section 9. Physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid colourless

Odour: solvent like

Odour threshold: N.A.

pH: 7.00

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 56 °C (133 °F)

Flash point: -18 °C (0 °F)

Flammability (Solid, Gas): N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour pressure: 23.00

Vapour density: 2.0

Relative density: 0.90 g/cm³

Solubility in water: 900 g/l (20°C)

Solubility in oil: Soluble

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: 540.00 °C

Decomposition temperature: N.A.

Section 10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

Section 11. Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

acetone; propan-2-one; propanone	a) acute toxicity	LD50 Oral Rat = 5800 mg/kg LD50 Skin Rabbit = 20000 mg/kg LC50 Inhalation Rat = 76 mg/l 4h LD50 Skin Rabbit > 15700 mg/kg LC50 Inhalation Rat = 50100 mg/m ³ 8h LD50 Oral Rat = 5800 mg/kg
toluene	a) acute toxicity	LC50 Inhalation Mouse = 5320 ppm LD50 Oral Rat = 5580 mg/kg LD50 Skin Rabbit = 12124 mg/kg LC50 Inhalation Rat 28,1 mg/l 4h LD50 Skin Rabbit = 12000 mg/kg LC50 Inhalation Rat = 12,5 mg/l 4h LD50 Oral Rat = 2600 mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

Section 12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Quantity	Component	Ident. Numb.	Ecotox Infos
>=50 - <75 %	acetone; propan-2-one; propanone	CAS: 67-64-1 - EINECS: 200-662-2 - INDEX: 606-001-00-8	<p>a) Aquatic acute toxicity : EC50 Daphnia = 6100 mg/L 48</p> <p>a) Aquatic acute toxicity : LC50 Fish = 5540 mg/L 96</p> <p>a) Aquatic acute toxicity : EC50 Algae = 302 mg/L 96</p> <p>a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96</p> <p>a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 4,74 mL/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 6210 mg/L 96h IUCLID</p> <p>a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 8300 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 10294 mg/L 48h EPA</p> <p>a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 12600 mg/L 48h IUCLID</p> <p>G : LC50 Avian Phasianus colchicus > 40000 ppm 5d IUCLID</p> <p>G : LC50 Avian Coturnix coturnix japonica > 40000 ppm 5d IUCLID</p> <p>d) Terrestrial toxicity : LC50 Worm Eisenia foetida 200 µg/cm2 48h IUCLID</p>
>=10 - <20 %	toluene	CAS: 108-88-3 - EINECS: 203-625-9 - INDEX: 601-021-00-3	<p>a) Aquatic acute toxicity : LC50 Daphnia = 3,78 mg/L 48</p> <p>a) Aquatic acute toxicity : EC50 Fish = 57,68 mg/L 96</p> <p>a) Aquatic acute toxicity : EC50 Algae = 134 mg/L 3</p> <p>a) Aquatic acute toxicity : LC50 Fish = 5,5 mg/L 96</p> <p>a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 15,22 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 12,6 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 5,89 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 14,1 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 5,8 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 11 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Oryzias latipes = 54 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 28,2 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 50,87 mg/L 96h EPA</p> <p>a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 5,46 mg/L 48h EPA</p> <p>a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 11,5 mg/L 48h IUCLID</p> <p>a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata > 433 mg/L 96h IUCLID</p>

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

Section 13. Disposal considerations

Disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Special precautions to be taken during disposal

No Data Available

Section 14. Transport information

UN number

1263

UN proper shipping name

NZS-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED 68781 213.213.127.242 MATERIAL (including paint thinning or reducing compound)

ADR-Shipping Name: PAINT or PAINT RELATED MATERIAL

IATA-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

NZS-Class: 3

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group, if applicable

NZS-Packing Group: II

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

Environmental hazards

Toxic ingredients quantity: 0.00

Very toxic ingredients quantity: 0.00

Marine pollutant: No

Environmental Pollutant: No

Special precautions for user

NZS-Subsidiary risks: -

NZS-Special Dispositions: 163

Road and Rail (ADR-RID):

ADR exempt: No

ADR-Label: 3

ADR-Hazard identification number: NA

ADR-Special Provisions: 163 367 640C 650

ADR-Transport category (Tunnel restriction code): 2 (D/E)

Air (IATA):

IATA-Passenger Aircraft: 353

IATA-Cargo Aircraft: 364

IATA-Label: 3

IATA-Subrisk: -

IATA-Erg: 3L

IATA-Special Provisions: A3 A72 A192

Sea (IMDG):

IMDG-Stowage Code: Category B

IMDG-Stowage Note: -

IMDG-Subrisk: -

IMDG-Special Provisions: 163 367

IMDG-EMS: F-E, S-E

Section 15. Regulatory information

HSNO Approval

HSNO approval number and group standard title:

HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Controls

Certified Handler

No Data Available

New Zealand Inventory of Chemicals (NZIoC)

All components are listed on the NZIoC Inventory.

Regulatory references

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Hazardous Substances (Classification) Regulations 2001.

Labelling of Hazardous Substances: Hazard and Precautionary Information (January 2012 EPA0094).

Assigning a Product to a HSNO Approval (May 2013/Revised June 2014).

Section 16. Other information

Safety Data Sheet dated: 5/3/2019 - version 1

Code	Description
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child if inhaled, in contact with skin and if swallowed.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure .
H373	May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Description of the HSNO Classification codes used in section 2 or 3:

Code	Description
3.1B	Flammable liquid - high hazard.
6.1E (aspiration)	Aspiration hazard.
6.3A	Substances that are irritating to the skin.
6.4A	Substances that are irritating to the eye.
6.8B	Substances that are suspected human reproductive or developmental toxicants.
6.9B (narcotic effects)	Narcotic effects.
6.9B (Repeated exposure)	Substances that are harmful to human target organs or systems (Repeated exposure).

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
IMDG: International Maritime Code for Dangerous Goods.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
CLP: Classification, Labeling, Packaging.
EINECS: European Inventory of Existing Commercial Chemical Substances.
INCI: International Nomenclature of Cosmetic Ingredients.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
GefStoffVO: Ordinance on Hazardous Substances, Germany.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
DNEL: Derived No Effect Level.
PNEC: Predicted No Effect Concentration.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.
KSt: Explosion coefficient.
HSNO: Hazardous Substances and New Organisms Act 1996.