Safety Data Sheet MAPEFLOOR I 300 SL/B

Safety Data Sheet dated: 18/06/2020 - version 1



Section 1. Identification of the substance and supplier

Product identifier

Mixture identification:

Trade name: MAPEFLOOR I 300 SL/B

Trade code: 905H999

Recommended use of the chemical and restrictions on use

Recommended use: Hardener for epoxy products

Uses advised against: Data not available

Supplier's details

Company: MBP (NZ) Ltd. - 88 Carbine Road, Mount Wellington, Auckland 1060, New Zealand Email: enquiries@MBPLtd.co.nz

Website: www.MBPLtd.co.nz - Phone: +64 9 921 1994 (Mon-Fri 9am-5pm) - Fax: +64 9 921 1993

Emergency phone number

New Zealand Poisons Centre: Ph: 0800 764 766

Section 2. Hazards identification

HSNO hazard classification

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2017.

HSNO classification:

6.1D (oral) H302 - Harmful if swallowed.

8.2B H314 - Causes severe skin burns and eye damage.

8.3A H318 - Causes serious eye damage.

6.5B H317 - May cause an allergic skin reaction.

9.1C H412 - Harmful to aquatic life with long lasting effects.

Hazard information

Pictograms and Signal Words



Danger

Hazard statements:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.
P260 Do not breathe mist/vapours/spray.
P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

 Date
 18/06/2020
 Production Name
 MAPEFLOOR I 300 SL/B
 Page n. 1 of 9

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see supplementary instructions on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Other hazards which do not result in a classification

No other hazards

Section 3. Composition/information on ingredients

Substances

N.A.

Mixtures

Mixture identification: MAPEFLOOR I 300 SL/B

Hazardous components within the meaning of HSNO Act and related classification

Quantity	Name	Ident. Numb.	Classification
≥25 - <50 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	6.1D (inhalation), H332; 6.1D (oral), H302; 6.4A, H319
≥25 - <50 %	Reaction products of 3- aminomethyl-3,5,5- trimethylcyclohexylamine and 4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane		8.2B, H314; 8.3A, H318; 6.5B, H317; 9.1C, H412
≥10 - <20 %	m-xylylenediamine	CAS:1477-55-0 EC:216-032-5	6.1D (inhalation), H332; 6.1D (oral), H302; 8.2B, H314; 6.5B, H317; 9.1C, H412
≥5 - <10 %	Salicylic acid	CAS:69-72-7 EC:200-712-3	6.1D (oral), H302; 8.3A, H318

Section 4. First aid measures

Description of necessary first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Give nothing to eat or drink.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

 Date
 18/06/2020
 Production Name
 MAPEFLOOR I 300 SL/B
 Page n. 2 of 9

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: == Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Methods and materials for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Section 7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Section 8. Exposure controls/personal protection

Workplace Exposure Standards

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term	Long Term	Short Term	Short Term	Behaviour Note
	туре			mg/m3		mg/m3		
m-xylylenediamine	NZL	NEW ZEALAND	С			0.100		

Predicted No Effect Concentration (PNEC) values

i i cui cicu i i cui cui cui	redicted no Effect concentration (1 NEC) values						
Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency	Remark		
benzyl alcohol	100-51-6	1 mg/l	Fresh Water				
		0.1 mg/l	Marine water				
		5.27 mg/kg	Freshwater sediments				
		0.527 mg/kg	Marine water sediments				
		39 mg/l	Microorganisms in sewage				

 Date
 18/06/2020
 Production Name
 MAPEFLOOR I 300 SL/B
 Page n. 3 of 9

treatments

		0.45 mg/kg	Soil
		2.3 mg/l	Intermittent release
m-xylylenediamine	1477-55-0	0.094 mg/kg	Fresh Water
		0.0094 mg/l	Marine water
		0.43 mg/kg	Freshwater sediments
		0.043 mg/kg	Marine water sediments
		0.152 mg/l	Intermittent release
		0.045 mg/kg	Soil
		10 mg/l	Microorganisms in sewage treatments
Salicylic acid	69-72-7	0.2 mg/l	Fresh Water
		1 mg/l	Intermittent release
		0.02 mg/l	Marine water
		1.42 mg/kg	Freshwater sediments
		0.14 mg/kg	Marine water sediments
		0.16 mg/kg	Soil
		162 mg/l	Microorganisms in sewage treatments

Derived No Effect Level. (DNEL)

Compon	ent	CAS-No.	Worker Worke Industr Profess y ional		Exposure Route	Exposure Frequency Remark	
benzyl al	zyl alcohol	100-51-6		20 mg/kg	Human Ora	l Short Term, systemic effects	
				4 mg/kg	Human Ora	l Long Term, systemic effects	
			110 mg/m3	27 mg/m3	Human Inhalation	Short Term, systemic effects	
			22 mg/m3	5.4 mg/m3	Human Inhalation	Long Term, systemic effects	
			40 mg/kg	20 mg/kg	Human Dermal	Short Term, systemic effects	
			8 mg/kg	4 mg/kg	Human Dermal	Long Term, systemic effects	
m-xylyle	nediamine	1477-55-0	0.33 mg/kg		Human Dermal	Long Term, systemic effects	
			1.2 mg/m3		Human Inhalation	Long Term, systemic effects	
Date	18/06/2020	Produ	uction Name M	1APEFLOC	OR I 300 SL/B		

MAPEFLOOR I 300 SL/B Page n. 4 of 9 Production Name

		0.2 mg/m3		Human Inhalation	Long Term, local effects
Salicylic acid	69-72-7	16 mg/m3	0.2 mg/m3	Human Inhalation	Long Term, local effects
			4 mg/kg	Human Oral	Short Term, systemic effects
		2 mg/kg	1 mg/kg	Human Dermal	Long Term, systemic effects
			4 mg/kg	Human Inhalation	Long Term, systemic effects
			1 mg/kg	Human Oral	Long Term, systemic effects

Engineering Controls

N.A.

Personal Protective Equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

N.A.

Section 9. Physical and chemical properties

Physical state: Liquid

Appearance and colour: Liquid transparent

Odour: ammonia Odour threshold: N.A.

pH: 8.50

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: 100 °C (212 °F) Flammability (Solid, Gas): N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour pressure: N.A. Vapour density: N.A.

Relative density: 1.00 g/cm3 Solubility in water: partly soluble

Solubility in oil: soluble

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Kinematic viscosity: N.A.

Particle characteristics: No data available

Viscosity: 100.00 cPs

Section 10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

Date 18/06/2020 Production Name MAPEFLOOR I 300 SL/B Page n. 5 of 9

Section 11. Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

benzyl alcohol a) acute toxicity LD50 Skin Rabbit = 2000 mg/kg

LD50 Oral Rat = 1620 mg/kg

LC50 Inhalation Rat = 11.00000 mg/l 4h

LD50 Skin Rabbit = 2 g/kg

LC50 Inhalation Rat = 8.8 mg/l 4h

LD50 Oral Rat = 1230 mg/kg

g) reproductive toxicity NOAEL Rat = 1072 mg/m3

m-xylylenediamine a) acute toxicity LD50 Oral Mouse = 930 mg/kg

LD50 Skin Rabbit = 2000 mg/kg

LC50 Inhalation Dust Rat = 2.4 mg/l 4h

LD50 Skin Rabbit = 2 g/kg

LC50 Inhalation Rat = 700 ppm 1h

LD50 Oral Rat = 660 mg/kg

Salicylic acid a) acute toxicity LC50 Inhalation Rat > 0.9 mg/l 1h

LD50 Oral Rat = 891 mg/kg LD50 Skin Rabbit > 2000 mg/kg

LD50 Skin Rat > 2 g/kg

LC50 Inhalation Rat > 900 mg/m3 1h

LD50 Oral Rat = 891 mg/kg LD50 Skin Rat > 2 g/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

Section 12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Component Ident. Numb. Ecotox Infos

benzyl alcohol CAS: 100-51-6 - EINECS: a) Aquatic acute toxicity: EC50 Daphnia = 230 mg/L 48

202-859-9 - INDEX: 603-

 Date
 18/06/2020
 Production Name
 MAPEFLOOR I 300 SL/B
 Page n. 6 of 9

a) Aquatic acute toxicity: LC50 Fish = 770 mg/L 1

a) Aquatic acute toxicity : EC50 Algae = 770 mg/L 72

a) Aquatic acute toxicity: LC50 Fish = 460 mg/L 96

a) Aquatic acute toxicity: EC50 Daphnia = 66 mg/L

b) Aquatic chronic toxicity: NOEC Daphnia = 51 mg/L - 21 d

a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 460 mg/L 96h

EPA

a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus = 10 mg/L 96h EPA

a) Aquatic acute toxicity: EC50 Daphnia water flea = 23 mg/L 48h

m-xylylenediamine CAS: 1477-55-0 -

EINECS: 216-032-5

a) Aquatic acute toxicity : EC50 Algae = 20 mg/L 72

a) Aquatic acute toxicity: EC50 Daphnia = 15.2 mg/L 48
 a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96
 a) Aquatic acute toxicity: LC50 Fish = 87.6 mg/L 96

a) Aquatic acute toxicity: LC50 Fish Oryzias latipes = 87.6 mg/L 96h ECHA

Salicylic acid CAS: 69-72-7 - EINECS: a) Aquatic acute toxicity: EC50 Daphnia = 870 mg/L 48

200-712-3

a) Aquatic acute toxicity: LC50 Fish = 90 mg/La) Aquatic acute toxicity: EC50 Algae > 100 mg/L 72

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 870 mg/L 48h EPA

Persistence and degradability

N.A.

Bioaccumulative potential

NΑ

Mobility in soil

N.A

Other adverse effects

N.A.

Section 13. Disposal considerations

Disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Special precautions to be taken during disposal

No data available

Section 14. Transport information

UN number

2735

UN proper shipping name

NZS-Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (modified cycloaliphatic polyamines - m-xylylendiamine)

ADR-Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (modified cycloaliphatic polyamines - m-xylylendiamine)

IATA-Technical name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (modified cycloaliphatic polyamines - m-xylylendiamine)

IMDG-Technical name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (modified cycloaliphatic polyamines - m-xylylendiamine)

Transport hazard class(es)

NZS-Class: 8
ADR-Class: 8
IATA-Class: 8
IMDG-Class: 8

Packing group, if applicable

NZS-Packing Group: II ADR-Packing Group: II IATA-Packing group: II

Date 18/06/2020 Production Name MAPEFLOOR I 300 SL/B Page n. 7 of 9

IMDG-Packing group: II

Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

Special precautions for user

NZS-Subsidiary risks: -

NZS-Special Dispositions: 274

Road and Rail (ADR-RID):

ADR-Label: 8

ADR-Hazard identification number: 80

ADR-Special Provisions: 274

ADR-Transport category (Tunnel restriction code): 2 (E)

Air (IATA):

IATA-Passenger Aircraft: 851 IATA-Cargo Aircraft: 855

IATA-Label: 8

IATA-Subsidiary hazards: -

IATA-Erg: 8L

IATA-Special Provisioning: A3 A803

Sea (IMDG):

IMDG-Stowage Code: Category A IMDG-Stowage Note: SG35 SGG18 IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274

IMDG-EMS: F-A, S-B

Section 15. Regulatory information

HSNO Approval

HSNO approval number and group standard title:

HSR002658 - Surface Coatings and Colourants (Corrosive) Group Standard 2006

HSNO Controls

Codo

Approved Handler

No data available

New Zealand Inventory of Chemicals (NZIoC)

All components are listed on the NZIoC Inventory.

Regulatory references

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Hazardous Substances (Classification) Regulations 2001.

Labelling of Hazardous Substances: Hazard and Precautionary Information (January 2012 EPA0094).

Assigning a Product to a HSNO Approval (May 2013/Revised June 2014).

Section 16. Other information

Safety Data Sheet dated: 18/06/2020 - version 1 Description

Code	Description
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Description of the HSNO Classification codes used in section 2 or 3:

Description Code

6.1D (inhalation) Substances that are acutely toxic - Harmful (inhalation). 6.1D (oral) Substances that are acutely toxic - Harmful (oral).

Date 18/06/2020 **Production Name** MAPEFLOOR I 300 SL/B Page n. 8 of 9 6.4A Substances that are irritating to the eye.
6.5B Substances that are contact sensitisers.

8.2B Substances that are corrosive to dermal tissue UN PGII.

8.3A Substances that are corrosive to ocular tissue.

9.1C Substances that are harmful in the aquatic environment.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

 ${\sf GefStoffVO:}\ \ {\sf Ordinance}\ \ {\sf on}\ \ {\sf Hazardous}\ \ {\sf Substances},\ {\sf Germany}.$

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

HSNO: Hazardous Substances and New Organisms Act 1996.

 Date
 18/06/2020
 Production Name
 MAPEFLOOR I 300 SL/B
 Page n. 9 of 9