

Safety Data Sheet

KERAPOXY CQ COMP. B

Safety Data Sheet dated: 4/24/2019 - version 1

Section 1. Identification of the substance and supplier

Product identifier

Mixture identification:

Trade name: KERAPOXY CQ COMP. B

Trade code: 9063999

Recommended use of the chemical and restrictions on use

Recommended use: Hardener for epoxy products

Uses advised against: Data not available

Supplier's details

Company: MBP (NZ) Ltd. - 88 Carbine Road, Mount Wellington, Auckland 1060, New Zealand Email: enquiries@MBPLtd.co.nz

Website: www.MBPLtd.co.nz - Phone: +64 9 921 1994 (Mon-Fri 9am-5pm) - Fax: +64 9 921 1993

Emergency phone number

New Zealand Poisons Centre: Ph: 0800 764 766

Section 2. Hazards identification

HSNO hazard classification

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2017.

HSNO classification:

6.1E (oral)	H303 - May be harmful if swallowed.
8.3A	H318 - Causes serious eye damage.
6.5B	H317 - May cause an allergic skin reaction.
9.1A	H410 - Very toxic to aquatic life with long lasting effects.
8.2C	H314 - Causes severe skin burns and eye damage.

Hazard information

Pictograms and Signal Words



Danger

Hazard statements:

H303	May be harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements:

P260	Do not breathe mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P321	Specific treatment (see supplementary instructions on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.

P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Other hazards which do not result in a classification

No other hazards

Section 3. Composition/information on ingredients

Substances

N.A.

Mixtures

Mixture identification: KERAPOXY CQ COMP. B

Hazardous components within the meaning of HSNO Act and related classification

Quantity	Name	Ident. Numb.	Classification
≥50 - <75 %	Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines	CAS:68410-23-1	8.3A, H318; 6.5B, H317; 9.1A, H410; 8.2C, H314; 9.1A, H400
≥20 - <25 %	3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	6.1D (dermal), H312; 6.1D (oral), H302; 8.2B, H314; 8.3A, H318; 6.5B, H317; 9.1C, H412
≥5 - <10 %	Phenol, styrenated	CAS:61788-44-1 EC:262-975-0	9.1B, H411
≥1 - <2.5 %	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	CAS:10563-29-8 EC:234-148-4	6.1D (oral), H302; 8.2A, H314; 6.5B, H317

Section 4. First aid measures

Description of necessary first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Most important symptoms/effects, acute and delayed

- Eye irritation
- Eye damages
- Skin Irritation
- Erythema

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Unsuitable extinguishing media:

- None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Methods and materials for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Section 7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Section 8. Exposure controls/personal protection

Workplace Exposure Standards

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC LIMIT	Exposure Route	Exposure Frequency	Remark
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	0,06 mg/l	Fresh Water		
		0,006 mg/l	Marine water		
		0,23 mg/l	Intermittent release		
		5,784 mg/kg	Freshwater sediments		
		0,578 mg/kg	Marine water sediments		
		1,121 mg/kg	Soil		
		3,18 mg/l	Microorganisms in sewage treatments		
Phenol, styrenated	61788-44-1	0,001 mg/l	Fresh Water		

		65778	Marine water sediments
		65778	Freshwater sediments
		0,17	Microorganisms in sewage treatments
		31525	Soil mg/kg
N'-(3-aminopropyl)-N,N- dimethylpropane-1,3- diamine	10563-29-8	0,0092	Fresh Water mg/l
		0,00092	Marine water mg/l
		0,092	Intermittent release
		18,1	Microorganisms in sewage treatments
		0,0336	Freshwater sediments

Derived No Effect Level. (DNEL)

Component	CAS-No.	Worker Industr y	Worker Profess ional	Consu mer	Exposure Route	Exposure Frequency	Remark
3-aminomethyl- 3,5,5- trimethylcyclohexyla mine	2855-13-2	20,1 mg/m3			Human Inhalation		
Phenol, styrenated	61788-44-1	11,02 mg/m3		2,717 mg/m3	Human Inhalation		Long Term, systemic effects
		6,25 mg/kg		3,125 mg/kg	Human Dermal		Long Term, systemic effects
				1,562 mg/kg	Human Oral		Long Term, systemic effects
N'-(3-aminopropyl)- N,N- dimethylpropane- 1,3-diamine	10563-29-8	3,7 mg/m3		0,65 mg/m3	Human Inhalation		Long Term, systemic effects
		7,5 mg/m3			Human Inhalation		Short Term, systemic effects
		3,7 mg/m3		0,65 mg/m3	Human Inhalation		Long Term, local effects
		0,67 mg/kg			Human Dermal		Long Term, systemic effects
				0,2 mg/kg	Human Oral		Long Term, systemic effects

Engineering Controls

N.A.

Personal Protective Equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:
N.A.

Section 9. Physical and chemical properties

Physical state: Liquid
Appearance and colour: gel light yellow
Odour: ammonia
Odour threshold: N.A.
pH: 11.00
Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.
Flash point: 100 °C (212 °F)
Flammability (Solid, Gas): N.A.
Upper/lower flammability or explosive limits: N.A.
Vapour pressure: 0.01
Vapour density: N.A.
Relative density: 1.06 g/cm³
Solubility in water: partly soluble
Solubility in oil: Soluble
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Kinematic viscosity: N.A.
Particle characteristics: No Data Available
Viscosity: 30,000.00 cPs

Section 10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

Section 11. Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

3-aminomethyl-3,5,5-trimethylcyclohexylamine	a) acute toxicity	LC50 Inhalation Dust Rat > 5,01 mg/l 4h LD50 Oral Rat = 1030 mg/kg LD50 Skin Rat > 2000 mg/kg
Phenol, styrenated	a) acute toxicity	LC50 Inhalation Vapour Mouse = 158,3 mg/l 4h LD50 Oral Rat > 2500 mg/kg LD50 Skin Rat > 2000 mg/kg
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	a) acute toxicity	LD50 Oral Rat = 1670 mg/kg

b) skin corrosion/irritation Skin Corrosive Skin Rabbit Positive
d) respiratory or skin sensitisation Skin Sensitization Skin Positive

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

Section 12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Quantity	Component	Ident. Numb.	Ecotox Infos
>=20 - <25 %	3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS: 2855-13-2 - EINECS: 220-666-8 - INDEX: 612-067-00-9	a) Aquatic acute toxicity : LC50 Fish = 110 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 23 mg/L 48 a) Aquatic acute toxicity : EC50 Daphnia = 388 mg/L 48 a) Aquatic acute toxicity : EC50 Algae > 50 mg/L 72 b) Aquatic chronic toxicity : NOEC Daphnia = 3 mg/L - 21 d
>=5 - <10 %	Phenol, styrenated	CAS: 61788-44-1 - EINECS: 262-975-0	a) Aquatic acute toxicity : EC50 Daphnia = 4,6 mg/L 48 a) Aquatic acute toxicity : EC50 Algae = 9,7 mg/L 72 a) Aquatic acute toxicity : LC50 Fish = 5,6 mg/L 96
>=1 - <2.5 %	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	CAS: 10563-29-8 - EINECS: 234-148-4	a) Aquatic acute toxicity : LC50 Fish = 215 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 9,2 mg/L 48 a) Aquatic acute toxicity : EC50 Algae = 21 mg/L 72

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

Section 13. Disposal considerations

Disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Special precautions to be taken during disposal

No Data Available

Section 14. Transport information

UN number

2735

UN proper shipping name

NZS-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine solution)

ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine solution)

IATA-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine solution)

IMDG-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine solution)

Transport hazard class(es)

NZS-Class: 8

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

Packing group, if applicable

NZS-Packing Group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Yes

Special precautions for user

NZS-Subsidiary risks: -

NZS-Special Dispositions: 223 274

Road and Rail (ADR-RID):

ADR-Label: 8

ADR-Hazard identification number: NA

ADR-Special Provisions: 274

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 852

IATA-Cargo Aircraft: 856

IATA-Label: 8

IATA-Subrisk: -

IATA-Erg: 8L

IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: SG35

IMDG-Subrisk: -

IMDG-Special Provisions: 223 274

IMDG-EMS: F-A, S-B

Section 15. Regulatory information

HSNO Approval

HSNO approval number and group standard title:

HSR002542 - Construction Products (Corrosive [8.2C]) Group Standard 2006

HSNO Controls

Certified Handler

No Data Available

New Zealand Inventory of Chemicals (NZIoC)

All components are listed on the NZIoC Inventory.

Regulatory references

Section 16. Other information

Safety Data Sheet dated: 4/24/2019 - version 1

Code	Description
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Description of the HSNO Classification codes used in section 2 or 3:

Code	Description
6.1D (dermal)	Substances that are acutely toxic - Harmful (dermal).
6.1D (oral)	Substances that are acutely toxic - Harmful (oral).
6.1E (oral)	Substances that are acutely toxic - May be harmful (oral).
6.5B	Substances that are contact sensitizers.
8.2A	Substances that are corrosive to dermal tissue UN PGI.
8.2B	Substances that are corrosive to dermal tissue UN PGII.
8.2C	Substances that are corrosive to dermal tissue UN PGIII.
8.3A	Substances that are corrosive to ocular tissue.
9.1A	Substances that are very ecotoxic in the aquatic environment.
9.1B	Substances that are ecotoxic in the aquatic environment.
9.1C	Substances that are harmful in the aquatic environment.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

HSNO: Hazardous Substances and New Organisms Act 1996.