

MAPEI

BALCONY COATINGS

INCLUDED PRODUCTS

Featured systems:

☐ Mapefloor PU FLEX

For additional information, please refer to the latest version of system and technical data sheet for each product.

PRODUCER

Mapei AS post@mapei.no www.mapei.no

WASTE MANAGMENT

Non-cured product is classified as hazardous waste. Cured or dried product should be disposed of in the same manner as other construction waste. Contact your local waste management facility.

ENVIROMENTAL INFORMATION

See safety datasheet for the featured product

MAINTENANCE

Surfaces should be cleaned when required. Avoid any furniture etc. with sharp legs as these may harm the membrane.

CLEANING

Clean when required. Use **Mapefloor Cleaner ED** (1- 3 % in water) or other weak alkaline cleaning agents (weak ammonia solution). Use a mop/ rag and rinse after use. Do not use abrasive paper etc. to remove marks. Red wine, coffee etc. can stain the surface if not removed while still wet.

PROTECTION WITH POLISH/WAX

To ease cleaning and to protect your flooring, polish or wax can be used on floors that have not been sprinkled with sand. Start with removing all trace of old polish or wax with **Mapefloor Wax Remover**. Then apply **Mapelux Lucida** (glossy) or **Mapelux Opaca** (matt) in accordance with each products datasheet.

SNOW CLEARING

When clearing snow, use equipment that has a plastic shovel, or use a brush. Avoid using any sharp objects.

ARTIFICIAL GRASS/DECKING

Decking and artificial grass can cause discolouration, and should be removed for the winter. Ensure that nails, screws etc. do not puncture the membrane.

SLIP PREVENTION

All non-permeable coatings will result in water and snow lying on the surface for longer than they would on a concrete floor. At such times the membrane may be slippery.

TILING/PAINTING

Construction:

Laying tiles on the membrane is not normally recommended. If tiles are to be laid, a suitable adhesive must be used, e.g. **Keralastic.**

REPAIRING DAMAGES

Any damage should always be repaired using the same material and system as originally used. Always contact the contractor before doing repairs

PRODUCTS AND COLOURS

Construction.
Area:
Pre-treatment:
Primary treatment:
Final-treatment(s):
Thickness/consumption:
Colour code(s):
PROJECT AND CONTRACTOR Project:
Project address:
Company:
Address:
Telephone:
Telephone:
E-mail: