

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

Safety Data Sheet dated 12/8/2017, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: ELASTOCOLOR TONACHINO PLUS 1,2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Water dispersion synthetic resin based paint

Uses advised against:

==

1.3. Details of the supplier of the safety data sheet

Supplier:

MAPEI AS - Vallsetvegen, 6 - 2120 Sagstua - Norway

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

MAPEI AS - phone: +47-62972000

fax: +47-62972099

www.mapei.no (office hours)

Giftinformasjonen – phone number: +47 22591300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

None

Hazard Statements:

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements:

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

terbutryn

2-octyl-2H-isothiazol-3-one

pyrithione zinc

1,2-benzisothiazol-3(2H)-one: May produce an allergic reaction.

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1): May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

The product is not classified dangerous according to CLP (EC 1272/2008); in fact it is a water based preparation in which there are no dangerous components .

The below mentioned crystalline silica, that originally is in the shape of inhalable powder with specific exposure limits, after its mixture into the preparation doesn't involve any exposure risk.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 5% - < 10% free crystalline silica ($\varnothing > 10 \mu$)

CAS: 14808-60-7, EC: 238-878-4

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

>= 0.1% - < 0.25% polyethylene glycol monooleylether

CAS: 9004-98-2, EC: 500-016-2

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 4.1/A1 Aquatic Acute 1 H400

>= 0.1% - < 0.25% pyrrhione zinc

CAS: 13463-41-7, EC: 236-671-3

⚠ 3.1/3/Inhal Acute Tox. 3 H331

⚠ 3.1/3/Oral Acute Tox. 3 H301

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 4.1/A1 Aquatic Acute 1 H400 M=100.

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=10.

>= 0.01% - < 0.05% free crystalline silica ($\varnothing < 10 \mu$)(*)

CAS: 14808-60-7, EC: 238-878-4

⚠ 3.9/1 STOT RE 1 H372

>= 0.005% - < 0.01% sodium hydroxide; caustic soda

REACH No.: 01-2119457892-27-XXXX, Index number: 011-002-00-6, CAS: 1310-73-2, EC: 215-185-5

⚠ 2.16/1 Met. Corr. 1 H290

⚠ 3.2/1A Skin Corr. 1A H314

>= 0.005% - < 0.01% 1,2-benzisothiazol-3(2H)-one

Index number: 613-088-00-6, CAS: 2634-33-5, EC: 220-120-9

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/A1 Aquatic Acute 1 H400

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

⚠ 3.1/4/Oral Acute Tox. 4 H302

>= 0.0015% - < 0.005% terbutryn

CAS: 886-50-0, EC: 212-950-5

⚠ 4.1/A1 Aquatic Acute 1 H400 M=100.

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=100.

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.4.2/1B Skin Sens. 1B H317

>= 0.00015% - < 0.0015% reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

Index number: 613-167-00-5, CAS: 55965-84-9, EC: 611-341-5

⚠ 3.2/1B Skin Corr. 1B H314

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/A1 Aquatic Acute 1 H400

⚠ 4.1/C1 Aquatic Chronic 1 H410

⚠ 3.1/3/Oral Acute Tox. 3 H301

⚠ 3.1/3/Dermal Acute Tox. 3 H311

⚠ 3.1/3/Inhal Acute Tox. 3 H331

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wash immediately with water for at least 10 minutes.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

A suspension of activated charcoal in water, or petroleum jelly may be administered.

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

The product does not present a fire hazard

Do not inhale explosion and combustion gases.

The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.

5.3. Advice for firefighters

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
 - Limit leakages with earth or sand.
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.
 - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - After the product has been recovered, rinse the area and materials involved with water.
 - Suitable material for taking up: absorbing material, organic, sand
 - Wash with plenty of water.
 - Retain contaminated washing water and dispose it.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
 - See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
 - Keep away from food, drink and feed.
 - Incompatible materials:
 - None in particular.
 - Instructions as regards storage premises:
 - Adequately ventilated premises.
 - Store above 5°C.
- 7.3. Specific end use(s)
 - None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
 - free crystalline silica ($\text{Ø} > 10 \mu$) - CAS: 14808-60-7
 - ACGIH - TWA(8h): 0.025 mg/m³ - Notes: (R), A2 - Pulm fibrosis, lung cancer
 - free crystalline silica ($\text{Ø} < 10 \mu$)(*) - CAS: 14808-60-7
 - ACGIH - TWA(8h): 0.025 mg/m³ - Notes: (R), A2 - Pulm fibrosis, lung cancer
 - EU - TWA(8h): 0.025 mg/m³ - Notes: A2 (R) - Pulm fibrosis, lung cancer
 - sodium hydroxide; caustic soda - CAS: 1310-73-2
 - ACGIH - STEL: Ceiling 2 mg/m³ - Notes: URT, eye, and skin irr
- DNEL Exposure Limit Values
 - sodium hydroxide; caustic soda - CAS: 1310-73-2

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

Worker Industry: 1 mg/m³ - Consumer: 1 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, local effects

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid
Colour:	various
Odour:	typical
Odour threshold:	N.A.
pH:	8,8
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	Not determined
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	Not determined
Flash point:	== °C
Evaporation rate:	Not determined
Vapour pressure:	N.A. kPa (23°C)
Relative density:	1,7 g/cm ³ (23°C)
Vapour density (air=1):	Not determined
Solubility in water:	dispersible
Solubility in oil:	insoluble
Viscosity:	72000 mPa.s (23°C)
Auto-ignition temperature:	== °C - No explosive or s pontaneous ignition in contact with air at room temperature
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A. - This product is a mixture
Explosive properties:	== - No components with explosive properties
Oxidizing properties:	N.A. - No component with oxidizing properties

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

Substance Groups relevant properties N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Route(s) of entry:

Ingestion: Yes

Inhalation: No

Contact: No

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

free crystalline silica ($\text{Ø} > 10 \mu$) - CAS: 14808-60-7

a) acute toxicity:

Test: LD50 - Route: Oral > 2000 mg/kg

Test: LD50 - Route: Skin > 2000 mg/kg

polyethylene glycol monooleylether - CAS: 9004-98-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 2700 mg/kg

pyrithione zinc - CAS: 13463-41-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 269 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Mouse > 1150 mg/kg

Test: LD50 - Route: Skin - Species: Mouse > 2000 mg/kg

Test: LD50 - Route: Oral - Species: Rat > 597 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit : Positive

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 457 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 2.36 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 660 mg/kg

Corrosive/Irritating Properties:

Eye:

The product can cause a temporary irritation by contact.

Carcinogenic Effects:

907BA0900/1

Page n. 6 of 10

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

No effects are known.

Mutagenic Effects:
No effects are known.

Teratogenic Effects:
No effects are known.

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Biodegradability: no data available on the preparation.

pyrithione zinc - CAS: 13463-41-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 0.0026 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 0.0082 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.0012 mg/l - Duration h: 120

sodium hydroxide; caustic soda - CAS: 1310-73-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 125 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 40.4 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 145 mg/l - Duration h: 24

c) Bacteria toxicity:

Endpoint: EC50 - Species: 19126 = 22 mg/l - Notes: 15 min

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 3.7 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.37 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 0.12 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.22 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 0.048 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72

Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28 d

Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21 d

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

- vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None
Not available data on the mixture

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover if possible. In so doing, comply with the local and national regulations currently in force.
91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.
Disposal of hardened product (EC waste code) : 08 01 12
Disposal of not hardened product (EC waste code) : 08 01 16
The suggested European waste code is just based on the composition of the product.
According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

- 14.1. UN number
Not classified as dangerous in the meaning of transport regulations.
UN Number: ==
- 14.2. UN proper shipping name
N.A.
- 14.3. Transport hazard class(es)
Rail/Road(RID/ADR): no dangerous good
ADR-Upper number: NA
Air (ICAO/IATA): no dangerous good
Sea (IMO/IMDG): no dangerous good
N.A.
- 14.4. Packing group
N.A.
- 14.5. Environmental hazards
Marine pollutant: No
N.A.
- 14.6. Special precautions for user
N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
No

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
Restrictions related to the product:
Restriction 3
Restriction 40
Restrictions related to the substances contained:
No restriction.

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

REACH Regulation (1907/2006) – All. XVII: N.A.
Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"
Directive 2000/39/CE and s.m.i. (Professional threshold limit)
Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)
Directive 105/2003/CE (Seveso III): N.A.
ADR Agreement – IMDG Code – IATA Regulation
VOC (2004/42/EC) : 30 g/l

MAL CODE: 1-3 (1993)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H315 Causes skin irritation.

H400 Very toxic to aquatic life.

H331 Toxic if inhaled.

H301 Toxic if swallowed.

H318 Causes serious eye damage.

H410 Very toxic to aquatic life with long lasting effects.

H372 Causes damage to organs through prolonged or repeated exposure.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

This safety data sheet has been completely updated in compliance to Regulation 2015/830.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of
Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical
Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Safety Data Sheet

ELASTOCOLOR TONACHINO PLUS 1,2

	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	Substance with a Union workplace exposure limit.
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List
N.A.:	Not available