

Safety Data Sheet

SILANCOLOR PITTURA PLUS

Safety Data Sheet dated 17/5/2015, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: SILANCOLOR PITTURA PLUS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Water dispersion synthetic resin based paint

1.3. Details of the supplier of the safety data sheet

Supplier:

MAPEI AS - Vallsetvegen, 6 - 2120 Sagstua - Norway

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

MAPEI AS - phone: +47-62972000

fax: +47-62972099

www.mapei.no (office hours)

Giftinformasjonen – phone number: +47 22591300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:

None

Hazard Statements:

None

Precautionary Statements:

None

Special Provisions:

None

Contents:

terbutryn

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-benzisothiazol-3(2H)-one

Pyrrithione zinc

Safety Data Sheet

SILANCOLOR PITTURA PLUS

octhiline (ISO); 2-octyl-2H-isothiazol-3-one: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

200 ppm 1,2-benzisothiazol-3(2H)-one

Index number: 613-088-00-6, CAS: 2634-33-5, EC: 220-120-9

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/A1 Aquatic Acute 1 H400

⚠ 3.1/4/Oral Acute Tox. 4 H302

95 ppm octhiline (ISO); 2-octyl-2H-isothiazol-3-one

Index number: 613-112-00-5, CAS: 26530-20-1, EC: 247-761-7

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/C1 Aquatic Chronic 1 H410

⚠ 3.1/3/Dermal Acute Tox. 3 H311

⚠ 3.1/3/Inhal Acute Tox. 3 H331

⚠ 3.2/1C Skin Corr. 1C H314

⚠ 4.1/A1 Aquatic Acute 1 H400

90 ppm free crystalline silica ($\varnothing > 10 \mu$)

CAS: 14808-60-7, EC: 238-878-4

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

15 ppm reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Index number: 613-167-00-5, CAS: 55965-84-9

⚠ 3.2/1B Skin Corr. 1B H314

⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

⚠ 4.1/A1 Aquatic Acute 1 H400

⚠ 4.1/C1 Aquatic Chronic 1 H410

⚠ 3.1/3/Oral Acute Tox. 3 H301

⚠ 3.1/3/Dermal Acute Tox. 3 H311

⚠ 3.1/3/Inhal Acute Tox. 3 H331

SECTION 4: First aid measures

4.1. Description of first aid measures

907J0920/1

Page n. 2 of 10

Safety Data Sheet

SILANCOLOR PITTURA PLUS

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wash immediately with water for at least 10 minutes.

In case of Ingestion:

A suspension of activated charcoal in water, or petroleum jelly may be administered.

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

None in particular.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

The product does not present a fire hazard

Do not inhale explosion and combustion gases.

The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Limit leakages with earth or sand.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Safety Data Sheet

SILANCOLOR PITTURA PLUS

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Fine dust may form explosive mixture with air. Keep away from open flames, heat and sparks.

Do not remove shrink film in hazardous locations (because of risk of static charging/discharge)

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Store above 5°C.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

free crystalline silica ($\text{Ø} > 10 \mu$) - CAS: 14808-60-7

ACGIH - LTE mg/m³(8h): 0.025 mg/m³ - Notes: A2 (R) - Pulm fibrosis, lung cancer

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Respiratory protection:

Not needed for normal use.

In case of insufficient ventilation use mask with B type filters (EN 14387).

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: paste

Colour: various

Odour: typical

Odour threshold: N.A.

pH: 8,5

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Safety Data Sheet

SILANCOLOR PITTURA PLUS

Flash point:	N.A.
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1,55 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	partly soluble
Solubility in oil:	N.A.
Viscosity:	40000 mPa.s (23°C)
Auto-ignition temperature:	N.A.
Explosion limits(by volume):	N.A.
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.
9.2. Other information	
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions
 - None
- 10.4. Conditions to avoid
 - Stable under normal conditions.
- 10.5. Incompatible materials
 - None in particular.
- 10.6. Hazardous decomposition products
 - None.

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects

Route(s) of entry:

Ingestion:	Yes
Inhalation:	No
Contact:	No

Toxicological information related to the product:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Mouse > 1150 mg/kg

Test: LD50 - Route: Skin - Species: Mouse > 2000 mg/kg

Test: LD50 - Route: Oral - Species: Rat > 597 mg/kg

octhlinone (ISO); 2-octyl-2H-isothiazol-3-one - CAS: 26530-20-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 500 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 311 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 0.78 mg/l - Duration: 4h

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

Safety Data Sheet

SILANCOLOR PITTURA PLUS

-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 53 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat 330 mg/m³ - Duration: 4h

Test: LC50 - Route: Inhalation - Species: Rat 2.36 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit 660 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

LD50 (oral rat): 67 mg/kg

LD50 (skin rat): > 140 mg/kg

Corrosive/Irritating Properties:

Eye:

The product can cause a temporary irritation by contact.

Sensitizing Properties:

No effects are known.

Carcinogenic Effects:

No effects are known.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

a) acute toxicity

b) skin corrosion/irritation

c) serious eye damage/irritation

d) respiratory or skin sensitisation

e) germ cell mutagenicity

f) carcinogenicity

g) reproductive toxicity

h) STOT-single exposure

i) STOT-repeated exposure

j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Biodegradability: not readily biodegradable

Biodegradability: no data available on the preparation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 3.7 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.37 mg/l - Duration h: 72

octhilinone (ISO); 2-octyl-2H-isothiazol-3-one - CAS: 26530-20-1

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 0.32 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.031 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 0.047 mg/l - Duration h: 96

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

-isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 0.16 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 0.19 mg/l - Duration h: 96

12.2. Persistence and degradability

Safety Data Sheet

SILANCOLOR PITTURA PLUS

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

List of substances dangerous for the environment and corresponding classification:

>= 0.25% - < 0.49% Pyrithione zinc

CAS: 13463-41-7

R50 Very toxic to aquatic organisms.

>= 0.1% - < 0.25% polyethylene glycol monooleyl ether

CAS: 9004-98-2

R50 Very toxic to aquatic organisms.

>= 0.1% - < 0.25% Zinc oxide

CAS: 1314-13-2

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EC50 (Daphnia): 0.17 mg/l (48 hr)

LC50 (Algae): 0.14 mg/l (72 hr)

LC50 (Fish): 0.14 mg/l (96 hr)

200 ppm 1,2-benzisothiazol-3(2H)-one

CAS: 2634-33-5

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 3.7 mg/l (48 hr)

EC50 (Algae): 0.37 mg/l (72 hr)

148 ppm Pyrithione zinc

CAS: 13463-41-7

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 0.05 mg/l (48 hr)

LC50 (Algae): 0.067 mg/l (72 hr)

LC50 (Fish): 0.06 mg/l (96 hr)

96 ppm octhlinone (ISO); 2-octyl-2H-isothiazol-3-one

CAS: 26530-20-1

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EC50 (Daphnia): 0.32 mg/l (48 hr)

EC50 (Algae): 0.031 mg/l (72 hr)

LC50 (Fish): 0.047 mg/l (96 hr)

30 ppm bronopol (INN); 2-bromo-2-nitropropane-1,3-diol

CAS: 52-51-7

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 1.1 mg/l (48 hr)

LC50 (Fish): 8.6 mg/l (96 hr)

EC50 (Daphnia) 48h - 1,4 mg/l

EC50 (Algae) 72h - 0,4 mg/l

LC50 (Fish) 96h - 41,2 mg/l

15 ppm reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

CAS: 55965-84-9

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EC50 (Daphnia): 0.16 mg/l (48 hr)

LC50 (Fish): 0.19 mg/l (96 hr)

15 ppm 2-methyl-2H-isothiazol-3-one (MIT)

Safety Data Sheet

SILANCOLOR PITTURA PLUS

CAS: 2682-20-4

R50 Very toxic to aquatic organisms.

EC50 (Daphnia): 1.6 mg/l (48 hr)

EC50 (Algae): 0.157 mg/l (72 hr)

LC50 (Fish): 6 mg/l (96 hr)

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

This material and its container must be disposed of as hazardous waste.

91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

SECTION 14: Transport information

14.1. UN number

UN Number: ==

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

Rail/Road(RID/ADR): no dangerous good

ADR-Upper number: NA

Air (ICAO/IATA): no dangerous good

Sea (IMO/IMDG): no dangerous good

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

Marine pollutant: No

N.A.

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 453/2010 (Annex I)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

No restriction.

Safety Data Sheet

SILANCOLOR PITTURA PLUS

REACH Regulation (1907/2006) – All. XVII: N.A.
Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"
Directive 2000/39/CE and s.m.i. (Professional threshold limit)
Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)
Directive 105/2003/CE (Seveso III): N.A.
ADR Agreement – IMDG Code – IATA Regulation
VOC (2004/42/EC) : 28 g/l

15.2. Chemical safety assessment
No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H400 Very toxic to aquatic life.
H302 Harmful if swallowed.
H410 Very toxic to aquatic life with long lasting effects.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H314 Causes severe skin burns and eye damage.
H301 Toxic if swallowed.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX'S - Dangerous properties of industrial materials
Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of
Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical

Safety Data Sheet

SILANCOLOR PITTURA PLUS

	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	European threshold limit value
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List