

# Aquaflex Roof and Aquaflex Roof HR

**READY-TO-USE ELASTIC MEMBRANES  
FOR WATERPROOFING**



Couldn't be  
easier!



## Ready-to-use liquid elastic membrane with fibres for seamless waterproofing layers on external exposed surfaces


### Characteristics and advantages:

- Resistant to atmospheric agents and UV rays;
- Easy to apply;
- Elastic with high crack-bridging capacity (300%);
- Excellent adhesion to a multitude of surfaces;
- Resistant to light foot traffic;
- Non-toxic and non-flammable;
- Supplied ready for use;
- CE marked in compliance with EN 1504-2 standards.

### Packaging

5 and 20 kg drums.

### Colours available (\*)



(\*) Due to the printing processes involved, colours should be taken as merely indicative of the shades of the actual product.



## Application examples:

### Bituminous sheath



Cleaning the substrate



Applying the primer



Applying the membrane

### Concrete structure



Prepared substrate



Applying the membrane



Completed application

### Ceramic flooring



Prepared substrate



Applying the membrane



Completed application

**Types of substrate where Aquaflex Roof and Aquaflex Roof HR may be applied:**



Bituminous sheath



Concrete structure



Ceramic flooring

## Fibre-filled liquid membrane in watery emulsion with high solar reflectance and thermal emissivity with a solar reflectance index (SRI) of 105

### Characteristics and advantages:

- 83% solar reflectance;
- 91% thermal emissivity;
- SRI (*Solar Reflectance Index*) 105;
- Reduces the surface temperature of roofs by 50% compared with a dark coloured covering;
- Resistant to atmospheric agents and UV rays;
- Easy to apply;
- Elastic with high crack-bridging capacity (300%);
- Excellent adhesion to a multitude of surfaces;
- Resistant to light foot traffic;
- Supplied ready for use;
- CE marked in compliance with EN 1504-2 standards.

### Packaging


20 kg drums.

### Colours available (\*)



(*high reflective*)





● **Technical documentation**

From the technical area menu you can view the technical documentation divided per product lines and type of document.

**HEADQUARTERS**  
**MAPEI SpA**  
Via Cafiero, 22 - 20158 Milan  
Tel. +39-02-37673.1  
Fax +39-02-37673.214  
Internet: [www.mapei.com](http://www.mapei.com)  
E-mail: [mapei@mapei.it](mailto:mapei@mapei.it)

