

Ultracoat Oil System

TWO-COMPONENT POLYURETHANE LACQUERS





**System for
the surface protection
of wooden flooring**

***Ultracoat High Traffic
or Ultracoat Soft Touch***
two-component lacquer finish

Ultracoat Oil Color
coloured urethane oil

rough wood

Ultracoat Oil Color and **Ultracoat Oil Plus** are suitable for all types of wood.

The range of colours available for **Ultracoat Oil** allow you to blend your parquet with the most daring solutions in interior decorating.

Ultracoat Oil Color and **Ultracoat Oil Plus** bring out the veins from deep down in the wood, while their light, golden shades bring out the natural beauty of parquet.

Ultracoat Oil Color and **Ultracoat Oil Plus Protection Systems**: simple and quick to apply, simple to maintain.

Apart from offering the widest choice of attractive finishes, **Ultracoat Oil Color** and **Ultracoat Oil Plus** used in combination with **Ultracoat** two-component, water-based finish are also suitable for wooden flooring in areas subjected to high and intense traffic, and guarantee a long service life to the finish.

All **Ultracoat Oil Color** and **Ultracoat Oil Plus** systems are easy to maintain.



Ultracoat Oil Color

Low-odour urethane oil finish for colouring wooden floors. It can be finished with a lacquer from the ULTRACOAT finishes.

Technical Data

Product Identity

Consistency:	fluid
Appearance:	coloured oil
Colours available:	white, black, walnut and American walnut, mahogany, cherry red
Density (g/cm ³):	0.8
Application temperature range:	+10°C - +25°C
Application:	roller, brush, pad or trowel
Removal time:	35 to 45 minutes
Buffing:	after 16 hours with a Ultracoat Black Pad
Ready for service:	after 3 days



Ultracoat Oil Plus

Low-odour urethane oil finish for wooden floors. It can be finished with a lacquer from the ULTRACOAT finishes.

Technical Data

Product Identity

Consistency:	fluid
Appearance:	oil
Colour:	neutral
Density (g/cm ³):	0.8
Application temperature range:	+10°C - +25°C
Application:	roller, brush, pad or trowel
Removal time:	35 to 45 minutes
Buffing:	after 16 hours with a Ultracoat Black Pad
Ready for service:	after 3 days



Technical documentation

From the technical area menu you can view the technical documentation divided per product lines and type of document.

HEAD OFFICE
MAPEI SpA
Via Cafiero, 22 - 20158 Milan
Tel. +39-02-37673.1
Fax +39-02-37673.214
Internet: www.mapei.com
E-mail: mapei@mapei.it



/mapeispa