

ECO ADHESIVES FOR QUALITY LIVING

ONE-COMPONENT SILYLATED ADHESIVES
WITH VERY LOW EMISSION OF VOLATILE
ORGANIC COMPOUNDS



ONE-COMPONENT SILYLATED ADHESIVES

The Mapei range of silylated polymer-based adhesives contains no water, solvent, amines and epoxy resin and has very low emission of volatile organic compounds (VOC).

The emission of methanol is currently a much-discussed subject. All Mapei silylated adhesives comply with highly restrictive German standards and are all rigorously below the emission limits specified for methanol. In particular, with **Ultrabond Eco S Plus** Mapei has even anticipated certification guidelines as it has zero methanol emissions.

The adhesives from the Mapei range comply with the requirements of 14293 European standards in the Soft and Hard categories and ISO in the Hard and Hard-Elastic category.

The adhesives from the Mapei range meet all the needs of users and are suitable for installing all types of wooden flooring, from pre-finished engineered flooring to all formats and types of solid wooden flooring, on any type of substrate suitable for wooden flooring.



Ultrabond Eco S958 1K



One-component Hard-Elastic silylated polymer based adhesive with zero solvent content and very low emission of volatile organic compounds. The perfect combination of the strength of its hardness and the advantages of its elasticity, compliant with ISO 17178 standards.

WHY USE ULTRABOND ECO S 958 1K:

particularly recommended for installing solid wood flooring.



Ultrabond Eco S Lite



One-component, lightweight, silylated polymer-based adhesive with zero solvent content and very low emission of volatile organic compounds.

WHY USE ULTRABOND ECO S LITE:

very low weight density leading to lower consumption rates per square metre during application, one drum weights 40% less than traditional drums.



Ultrabond Eco S Plus



One-component, silylated polymer-based adhesive of new generation and technology with very low emission of volatile organic compounds and zero methanol emissions.

WHY USE ULTRABOND ECO S PLUS:

zero methanol emissions; safer for the health of the installer and greater respect for the environment.



Technical Data	
Product identity	
Consistency:	creamy paste
Colour:	beige
EMICODE:	EC1 R Plus
Blauer Engel:	RAL - UZ 113
Shear strength according to ISO 17178:	2.3



www.blauer-engel.de/uz113

Technical Data	
Product identity	
Consistency:	creamy paste
Colour:	light grey
EMICODE:	EC1 R Plus
Blauer Engel:	RAL - UZ 113



www.blauer-engel.de/uz113

Technical Data	
Product identity	
Consistency:	creamy paste
Colour:	ivory
EMICODE:	EC1 R Plus



EVERYTHING'S OK WITH MAPEI

HEAD OFFICE

MAPEI SpA

Via Cafiero, 22 - 20158 Milan

Tel. +39-02-37673.1

Fax +39-02-37673.214

Internet: www.mapei.com

E-mail: mapei@mapei.it

