SUBSTRATE preparation products







Ultraplan Renovation

Planex HR Planex HR Maxi

Planiprep 4 LVT











FIBRE-REINFORCED SELF-LEVELLING COMPOUND

- Layers 3 to 40 mm thick per application.
- For all types of floor.
- For various types of substrate:
 new or old concrete substrates;
 - stone, terrazzo, ceramic;
 - various types of wood-based substrates and panels.





- Also for external use.
- Also for wet area.
- Also for substrates subject to rising damp.
- For all types of floor.



READY-TO-USE SKIM-COATING COMPOUND AND GROUT SMOOTHER

- Levelling off existing substrates with grouts before installing LVT.
- Levelling off and grouting various types of substrate and panels (wood, gypsum, plasterboard, fibre-cement, etc.).
- No preparation and mixing
- Dries in 2 hours.



READY-TO-USE GROUT SMOOTHER: **EASY TO REMOVE WITHOUT LEAVING** ANY RESIDUAL

- Levelling off existing substrates with grouts before installing loose-lay LVT.
- No preparation and mixing.
- Easy to remove, leaves no traces.









25 kg bags 10 kg drums 10 kg drums



HEAD OFFICE MAPEI SpA

Via Cafiero, 22 - 20158 Milan

Tel. +39-02-37673.1

Fax +39-02-37673.214

Internet: www.mapei.com E-mail: mapei@mapei.it

