# Ultrabond Eco Tack LVT

PRODUCTS FOR LVT "LUXURY VINYL TILES"







## Ultrabond Eco Tack LVT

Permanent tack adhesive in water dispersion for loose lay floorings in planks and tiles







### WHERE TO USE

Non-permanent bonding of loose laid textile and resilient flooring. Particularly suitable for effect loose lay vinyl floorings in planks and tiles.

### **ADVANTAGES**

- When dry, the film of **Ultrabond Eco Tack LVT** remains tacky so that loose lay floorings may be held in place and then easily removed and/or replaced;
- Suitable for all types of substrates normally used in the building industry, on existing floorings or on any type of raised floors;
- Ultrabond Eco Tack LVT is particularly suitable for installing loose laid floorings in planks, in that it reduces their tendency to shrink at the ends and between the joints.

### **PACKAGING**

The product is supplied in 15 kg tubs.





Technical Data (typical values)

Product Identity				
Consistency:	liquid			
Colour:	light beige			
Density (g/cm³):	1.05			
pH:	9.5			
Dry solids content (%):	50			
Brookfield viscosity (mPa·s):	700 (rotor 4 - 20 rpm)			
Emicode:	EC 1 - very low emission			
Application data (at 23°C - 50% R.H.)				
Application temperature range:	from +15°C to +35°C			
Waiting time:	install flooring when the adhesive becomes transparent (after 2-12 hours, depending on surrounding conditions and absorption of the substrate)			
Final performance				
Resistance to passage of	good			
wheelchairs:				
Heated floors:	suitable			
Resistance to humidity:	good			
Resistance to ageing:	excellent			







#### Technical documentation

From the technical area menu you can view the technical documentation divided per product lines and type of document

#### HEAD OFFICE MAPEI SpA

Via Cafiero, 22 - 20158 Milan

Tel. +39-02-37673.1

Fax +39-02-37673.214

Internet: www.mapei.com E-mail: mapei@mapei.it





/mapeispa

