

# Mapei's Innovative Silicone Sealants







### Mould-resistant, acetic, pure silicone sealant for general use.

- Suitable for interior and exterior applications
- Suitable for swimming pools
- Adheres perfectly to all kind of substrates
- Primer FD can be used as a bond enhancer where required
- Excellent durability and high elasticity
- Movement accommodation up to 25%
- Available in transparent and 34 colours coordinated with 'Mapei Coloured Grouts' range
- Available in 310 ml cartridges (12 in a box)
- 24 months of shelf life in a cool and dry place in original cartridges

### In compliance with:

ISO 11600, F-25-LM BS 5889 type B ASTM C920 EN 15651-1 TT-S-00230 C EN 15651-2 EN 15651-3 TT-S-001543 A DIN 18540, T.2, Class E





### **Available Colours**





### Neutral mould-resistant silicone sealant for natural stone and marble.

- Non staining
- Suitable for internal and external grout and expansion joints
- Also suitable for sealing between:
  - pre-fabricated panels
  - Window/door fittings and wall surrounds
  - Pipe-work and walls
- Good bond on most of the substrate even without a primer. Primer FD must be applied in the case of prolonged immersion in water
- ☐ Available in transparent and 9 colours coordinated with 'Mapei Coloured Grouts' range
- Available in 310 ml cartridges (12 in a box)
- □ 18 months of shelf life in a cool and dry place in original cartridges

### In compliance with:


BS 5889 type A ASTM C1248 ASTM C920 class 25 TT-S-00230 C class A TT-S-001543 A class A

DIN 18545-2, class E DIN 18540 ISO 11600, F-25-LM ISO 11600, G-25-LM





### **Available Colours**



## Mapesil Z Plus



### Mould-resistant acetic silicone sealant for sanitary fittings.

- Suitable for mould resistant seals in bathrooms, kitchens, laundry rooms and damp environments.
- Suitable for making seals in the building, automobile, naval and industrial sectors
- Suitable for sealing;
  - sanitary fittings e.g. pipe fittings, bath-tubs, showers and saunas.
  - Greenhouses.
  - Glass with a U profile
  - between glass and window frames
  - air and water vents
  - portholes
- Available in transparent and 4 colours coordinated with 'Mapei Coloured Grouts' range
- Available in 280 ml cartridges (12 in a box)
- 18 months of shelf life in a cool and dry place in original cartridges


In compliance with:


EN 15651-1

EN 15651-3



### **Available Colours**







### **HOW TO SEAL ELASTIC JOINTS**



All the surfaces to be sealed must be dry, sound and free of all traces of substances that could affect adhesion of the sealant.



Place masking tape along the edges of the joint to make it easier to clean the tiles.



Insert *Mapefoam* cord in the joint to set the correct depth and to make sure the sealant sticks only to the sides of the joint and not to the bottom.



Apply primer with a brush on the surface of the areas of the joint to be sealed and leave it to dry for a few minutes.



Cut the tip off the cartridge and insert the cartridge in a sealant extrusion gun to extrude and apply the appropriate MAPEI sealant in the joint protected with masking tape.



Finish off the surface of the sealant with a suitable damp tool or a tool dipped in soapy water before skin forms on the surface. Remove the masking tape from along the sides of the joint.

### **SEALING CRITICAL AREAS**



Seal around the grate of floor drains with *Mapesil* **AC**.



Sealing in correspondence with skirting board-wall fillet joints with *Mapesil AC*.



Seal joints in stone and on external façades with *Mapesil LM*.

## UNITED ARAB EMIRATES MAPEI CONSTRUCTION CHEMICALS L.L.C

P.O. Box: 73869, Dubai - United Arab Emirates Tel: +971 4 815 6666 info@mapei.ae - www.mapei.ae

### QATAR Mapei Doha L.L.C

P.O Box: 32522, Doha - Qatar Tel: +974 4423 1308 / Fax: +974 4423 1100 info@mapei.qa - www.mapei.qa

### **EGYPT**

### MAPEI EGYPT FOR CONSTRUCTION CHEMICALS S.A.E

Cairo - Egypt Tel: +20 2 2537 0000 / Fax: +20 2 2537 0004 info@mapei.eg - www.mapei.eg

