

# ULTRABOND ECO V4 EVOLUTION

ALL THE BEST CHARACTERISTICS  
OF OUR BEST ADHESIVES  
IN ONE FORMULATION

**THE ALL-IN-ONE  
UNIVERSAL ADHESIVE**  
BETTER THAN THE BEST



# ALL THE BEST CHARACTERISTICS OF OUR BEST ADHESIVES IN ONE FORMULATION



**PVC, NON-PVC PU, PO  
LVT, RUBBER  
TEXTILES, LINOLEUM**



**MAPEI N. 1, 2, 3  
TKB A1, A2, B1, B2  
ROLLER**



[www.emicode.com](http://www.emicode.com)



[www.blauer-engel.de/uz113](http://www.blauer-engel.de/uz113)



\* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

# Ultrabond Eco V4 Evolution



## APPLICATIONS:

- heterogeneous and homogeneous PVC tiles and rolls;
- LVT, SPC, and rigid LVT;
- modular LVT;
- cushion floors (CV) and multi-layered PVC;
- rubber flooring (sheets and tiles, including multi-layered flooring with rubber or foam soundproof backing).

## Also suitable for bonding:

- semi-flexible vinyl tiles (VCT);
- carpet with any type of backing (latex, PVC and polyurethane foam, natural jute, Action Bac®, etc.);
- flotex flooring;
- linoleum with natural jute backing;
- linoleum with synthetic jute, polyolefin and polyurethane backing;
- chloride-free and polyolefin based (PO) flooring;
- polyurethane based (PU) flooring;
- PVC and rubber wall coverings;
- indoor sports surfaces.

## Universal adhesive with strong, high initial hold and extended open time.

High performance adhesive for all types of resilient and textile flooring. Suitable for internal walls and floors in residential, commercial and industrial surroundings.

## PROPERTIES OF THE PRODUCT:

- Easy to apply
- Also suitable for use as "pressure sensitive" adhesive for the installation of dimensionally stable floorings
- Rapid, strong initial tack and adhesion
- Lower waiting times
- Very long open and working times
- Strong and tough final adhesion

## TECHNICAL DATA: (AT +23°C - 50% R.H.)

Product identity	
Consistency:	creamy paste
Colour:	light beige
Waiting time:	10-20 mins*
Open time:	40-50 mins. (70-80 mins. if used as "PRESSURE SENSITIVE" adhesive)*
Set to foot traffic:	3-5 hours*
Ready for use:	24-48 hours
Storage:	12 months. Do not expose to freezing weather for long periods
Consumption:	200-450 g/m <sup>2</sup>
Packaging:	16 kg and 5 kg drums

\* Times vary depending on environmental temperature, relative humidity, absorption of the substrate, type of flooring and consumptions

# EVERYTHING'S OK WITH MAPEI

## HEAD OFFICE

**MAPEI SpA**

Via Cafiero, 22 - 20158 Milan

Tel. +39-02-37673.1

Fax +39-02-37673.214

Internet: [www.mapei.com](http://www.mapei.com)

E-mail: [mapei@mapei.it](mailto:mapei@mapei.it)