Ultracoat Soft Touch

PRODUCTS FOR **PROTECTING** UNFINISHED **WOODEN FLOORS**









Ultracoat Soft Touch



Ultracoat Soft Touch Base, one-component, water-based primer for preparing wooden floors before applying Ultracoat Soft Touch Finish. Product with low emission of volatile organic compounds GEV EMICODE EC1 and no NMP

WHERE TO USE

Preparation of solid and engineered unfinished wooden floors and floors requiring repair.

TECHNICAL CHARACTERISTICS

Ultracoat Soft Touch Base is a one-component, rapid drying, water-based primer characterized by its excellent covering properties, rapid drying, ease of buffing and ease of application which reduces the problem of overlapping.









Ultracoat Soft Touch Finish, two-component, water-based, 100% polyurethane varnish with no NMP and with low emission of volatile organic compounds, GEV EMICODE EC1 R. Natural, soft finishing for protecting wooden floors in residential and commercial environments

WHERE TO USE

Highly protective, wear and abrasion resistant finish for solid or engineered unfinished wooden floors requiring repair in residential or commercial environments, including those subjected to high level of foot traffic.

TECHNICAL CHARACTERISTICS

Ultracoat Soft Touch Finish is two-component, water-based, 100% polyurethane, aliphatic (non yellowing) varnish, with high resistance to abrasion and to scuff marks from rubber-soled shoes.

It also gives timber floors an attractive "natural wood" finish which is soft to the touch: all the floors treated with this varnish have a natural finish similar to impregnation products such as oil or wax.









Technical documentation

From the technical area menu you can view the technical documentation divided per product lines and type of document.

HEAD OFFICE MAPEI S.p.A.

Via Cafiero, 22 - 20158 Milan Tel. +39-02-37673.1 Fax +39-02-37673.214

Internet: www.mapei.com E-mail: mapei@mapei.it



