

HARD CONCRETE, LACKER AND WATERPROOFING

INCLUDED PRODUCTS

- Mapetop N
- Mapetop S
- Concrete Sealer
- Mapecure Hardener
- Mapecrete Li Hardener
- Primer N
- Mapeprimer W
- Mapefloor PU TC Transparent
- Mapefloor Finish 52 W
- Mapefloor Finish 58 W
- Mapefloor Finish 630
- Mapecrete Stain Protection

For additional information, please refer to the latest version of system and technical data sheet for each product.

PRODUCER

Mapei AS
 post@mapei.no
www.mapei.no

WASTE MANAGEMENT

Non-cured product is classified as hazardous waste. Cured or dried product should be disposed of in the same manner as other construction waste. Contact your local waste management facility.

ENVIRONMENTAL INFORMATION

See safety datasheet for the featured product.

MAINTENANCE

Surfaces should be cleaned when required. All final treatment will with time be subject to abrasion, reduction of gloss etc. dependent on the use. Changes of colors may occur – both from exposure to sunlight and different fluids. Any damage should be repaired as soon as possible.

CLEANING

Floors can be cleaned either by hand, with pressure cleaners or machine dependent on the construction. Use **Mapefloor Cleaner ED** (1- 3 % in water) as a cleaning agent. Other weak alkaline cleaning agents may be used but it's recommended that there is done a trial area to evaluate if it's suited for the flooring. If using a machine soft pads/brushes should be used to avoid abrasion.

REMOVING OF RUBBERMARKS ETC.

Removing of rubber marks etc. must normally be done with special cleaning agents. There should be done test to avoid degeneration of gloss.

PROTECTION WITH POLISH/WAX

To ease cleaning and to protect your flooring, polish or wax can be used on floors that have not been sprinkled with sand. Start with removing all trace of old polish or wax with **Mapefloor Wax Remover**. Then apply **Mapelux Lucida** (glossy) or **Mapelux Opaca** (matt) in accordance with each products datasheet.

REPAIRING DAMAGES

Before repairing damages the cause of the damage should be identified. Any damages should always be repaired using the same material and system as originally used. Cracks or loose materials may be repaired with **Mapepoxy BI-IMP** and **Mapepoxy L**. Always contact the contractor before doing repairs.

PRODUCTS AND COLOURS

Construction: _____

Area: _____

Pre-treatment: _____

Primary treatment: _____

Final-treatment(s): _____

Thickness/consumption: _____

Colour code(s): _____

PROJECT AND CONTRACTOR

Project: _____

Project address: _____

Company: _____

Address: _____

Telephone: _____

Telephone: _____

E-mail: _____

Date: _____