Safety Data Sheet PLANITOP 15 RAPID

Safety Data Sheet dated: 06/11/2021 - version 2 Date of first edition: 05/04/2021



1. Identification

Product identifier

Mixture identification: Trade name: PLANITOP 15 RAPID Other means of identification Trade code: 9027569

Recommended use and restrictions on use

Recommended use: Cement based levelling mortar Restrictions on use: N.A.

Supplier's details

Company: MAPEI INC. (Canada) 2900 Francis-Hughes Avenue H7L 3J5 - Laval - QC - CAN

Emergency phone number

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. Hazard identification



Classification of the product

Label elemente	
STOT RE 1	Causes damage to organs through prolonged or repeated exposure if inhaled.
STOT SE 3	May cause respiratory irritation.
Carc. 1A	May cause cancer if inhaled.
Skin Sens. 1	May cause an allergic skin reaction.
Eye Dam. 1	Causes serious eye damage.
Skin Corr. 1A	Causes severe skin burns and eye damage.

Label elements

Pictograms and Signal Words



Hazard statements:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H350	May cause cancer if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements:

,	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P310 Immediately call a doctor. P321 Specific treatment (see supplementary instructions on this label) If skin irritation or rash occurs: Get medical advice/attention. P333+P313 P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with applicable regulations. **Other hazards**

None

Ingredient(s) with unknown acute toxicity

None

3. Composition/information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

List of	f compo	nents
---------	---------	-------

List of com	policito			
Concentra tion (% w/w)	Name	Ident. Numb.	Classification	Registration Number
25-50 %	silica sand; quartz	CAS:14808-60-7	STOT RE 1, H372; Carc. 1A, H350	
	portland cement; cement, portland, chemicals		STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314	
2.5-5 %	calcium oxide; quicklime		Skin Irrit. 2, H315; STOT SE 3, H335; Eye Dam. 1, H318	
	aluminum sulfate; dialuminum sulfate		Eye Dam. 1, H318; Met. Corr. 1, H290; Aquatic Acute 3, H402	

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

(see paragraph 4.1)

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases. Burning produces heavy smoke. Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. Exposure controls/personal protection Control parameters

List of components with OEL value

Component OE Typ	EL Country pe	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note	
---------------------	------------------	---------	-----------------------	---------------------	------------------------	----------------------	-----------	------	--

silica sand; quartz	ACGIH		0,025		A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
portland cement; cement portland, chemicals	, OSHA		15		
	OSHA		5		
	ACGIH		1		A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;
	ACGIH		1		A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma
	MAK	AUSTRIA	5		
	MAK	SWITZERLAND	5		
calcium oxide; quicklime	OSHA		5		
	ACGIH		2		upper respiratory tract irritation;
	MAK	GERMANY	1		
	ACGIH		2		upper respiratory tract irritation
	MAK	AUSTRIA	1	4	
	MAK	SWITZERLAND	2		

Appropriate engineering controls

N.A.

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment. Use adequate protective respiratory equipment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Solid Appearance and colour: powder Grey Odour: cement like Odour threshold: No data available pH: No data available pH (water dispersion, 10%): 12.60 Melting point / freezing point: No data available Initial boiling point and boiling range: No data available Flash point: No data available Evaporation rate: No data available Upper/lower flammability or explosive limits: No data available Vapour density: No data available Vapour pressure: No data available Relative density: 1.26 g/cm3 Solubility in water: partly soluble Solubility in oil: No data available Partition coefficient (n-octanol/water): No data available Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity: No data available Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

silica sand; quartz	a) acute toxicity	LD50 Oral Rat = 500 mg/kg
calcium oxide; quicklime	a) acute toxicity	LD50 Oral Rat = 500 mg/kg
aluminum sulfate; dialuminum sulfate	a) acute toxicity	LD50 Oral Rat = 1930 mg/kg
		LD50 Oral Rat = 1930 mg/kg
		LD50 Oral Rat = 1930 mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

i) STOT-repeated exposure

j) aspiration hazard

Substance(s) listed on the IARC Monographs:

Group 1

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

silica sand: quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
silica sand; quartz	CAS: 14808-60- 7	a) Aquatic acute toxicity: LC50 carp > 10000,00000 mg/L 72h
calcium oxide; quicklime	CAS: 1305-78-8	a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 1070 mg/L 96h IUCLID
aluminum sulfate; dialuminum sulfate	CAS: 10043-01- 3	a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 27,9 mg/L 96h ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

TDG-UN number: N.A. ADR-UN number: N.A. DOT-UN Number: N.A.

IATA-Un number: N.A. IMDG-Un number: N.A. UN proper shipping name TDG-Shipping Name: N.A. ADR-Shipping Name: N.A. DOT-Proper Shipping Name: N.A. IATA-Technical name: N.A. IMDG-Technical name: N.A. Transport hazard class(es) TDG-Class: N.A. ADR-Class: N.A. DOT-Hazard Class: N.A. IATA-Class: N.A. IMDG-Class: N.A. **Packing group** TDG-Packing Group: N.A. ADR-Packing Group: N.A. DOT Packing Group: N.A. IATA-Packing group: N.A. IMDG-Packing group: N.A. **Environmental hazards** Marine pollutant: No Environmental Pollutant: N.A. Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code) N.A. Special precautions in connection with transport or conveyance TDG: TDG Special provisions: N/A Department of Transportation (DOT): N.A. Road and Rail (ADR-RID) : N.A. Air (IATA): N.A. Sea (IMDG) : N.A.

15. Re	gulatory information		
Canada	a - Federal regulations		
DSL - D	omestic Substances List		
	DSL Inventory:		
	All the substances are listed in the	DSL.	
NDSL -	Non Domestic Substances List		
	NDSL Inventory:		
	No substances listed		
NPRI -	National Pollutant Release Inve	ntory	
	Substances listed in NPRI:		
	No substances listed		
USA -	Federal regulations		
TSCA -	Toxic Substances Control Act		
	TSCA inventory:		
	All the components are listed on th	e TSCA inventory	
	TSCA listed substances:		
	silica sand; quartz	is listed in TSCA	Section 8b
	portland cement; cement, portland, chemicals	is listed in TSCA	Section 8b
	calcium oxide; quicklime	is listed in TSCA	Section 8b
	aluminum sulfate; dialuminum sulfate	is listed in TSCA	Section 8b

	Superfund Amendments and Reauthorization Act Section 302 - Extremely Hazardous Substances:
	No substances listed
S	Section 304 - Hazardous substances:
a	aluminum sulfate; dialuminum sulfate
S	Section 313 - Toxic chemical list:
Ν	No substances listed
CERCLA -	- Comprehensive Environmental Response, Compensation, and Liability Act
S	Substance(s) listed under CERCLA:
а	aluminum sulfate; dialuminum sulfate Reportable quantity: 5000 pounds
CAA - Cle	ean Air Act
C	CAA listed substances:
Ν	No substances listed
CWA - Cl	ean Water Act
C	CWA listed substances:
	aluminum sulfate; dialuminum is listed in CWA Section 311 sulfate
	tate specific regulations a Proposition 65
	Substance(s) listed under California Proposition 65:
	silica sand; guartz Listed as carcinogen
	usetts Right to know
	Substance(s) listed under Massachusetts Right to know:
	silica sand; quartz
	portland cement; cement, portland, chemicals
	calcium oxide; quicklime
	aluminum sulfate; dialuminum sulfate
	vania Right to know
_	Substance(s) listed under Pennsylvania Right to know:
	silica sand; quartz
	portland cement; cement, portland, chemicals
	calcium oxide; quicklime
	aluminum sulfate; dialuminum sulfate
	sey Right to know
	Substance(s) listed under New Jersey Right to know:
	silica sand; quartz
	portland cement; cement, portland, chemicals
	calcium oxide; quicklime
	aluminum sulfate; dialuminum sulfate

16. Other information

Safety Data Sheet dated: 6/11/2021 - version 2

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description					
H290	May be corrosive to	May be corrosive to metals.				
H314	Causes severe skin l	Causes severe skin burns and eye damage.				
H315	Causes skin irritation	Causes skin irritation.				
H317	May cause an allergi	May cause an allergic skin reaction.				
H318	Causes serious eye damage.					
Print date	11/10/2022	Production Name	PLANITOP 15 RAPID			

- H335 May cause respiratory irritation.
- H350 May cause cancer.
- H350 May cause cancer if inhaled.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H372 Causes damage to organs through prolonged or repeated exposure if inhaled.
- H402 Harmful to aquatic life

Legend to abbreviations and acronyms used in the safety data sheet:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- CLP: Classification, Labeling, Packaging.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- INCI: International Nomenclature of Cosmetic Ingredients.
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- LC50: Lethal concentration, for 50 percent of test population.
- LD50: Lethal dose, for 50 percent of test population.
- DNEL: Derived No Effect Level.
- PNEC: Predicted No Effect Concentration.
- TLV: Threshold Limiting Value.
- TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
- STEL: Short Term Exposure limit.
- STOT: Specific Target Organ Toxicity.
- WGK: German Water Hazard Class.
- KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 12. ECOLOGICAL INFORMATION